

### **OIL ANALYSIS REPORT**

#### Sample Rating Trend



# KAESER BSD 50 7503048 (S/N 1070)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

#### DIAGNOSIS

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is a moderate amount of particulates present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA011656	KCP52111	KCP36621
Sample Date		Client Info		08 Jan 2024	18 Jan 2023	20 May 2021
Machine Age	hrs	Client Info		17148	13426	6300
Oil Age	hrs	Client Info		0	3000	2000
Oil Changed		Client Info		N/A	Changed	Changed
Sample Status				ATTENTION	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	1	1	<1
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>10	2	2	<1
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	17	9	3
Tin	ppm	ASTM D5185m	>10	<1	<1	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	22
Barium	ppm	ASTM D5185m	90	0	1	<1
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	100	10	25	44
Calcium	ppm	ASTM D5185m	0	0	0	0
Phosphorus	ppm	ASTM D5185m	0	31	11	2
Zinc	ppm	ASTM D5185m	0	165	95	14
Sulfur	ppm	ASTM D5185m	23500	19168	20086	20297
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	2	2
Sodium	ppm	ASTM D5185m		0	7	16
Potassium	ppm	ASTM D5185m	>20	3	7	1
Water	%	ASTM D6304	>0.05	0.009	0.014	0.023
ppm Water	ppm	ASTM D6304	>500	100	144.5	232.1
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		9648	14636	15710
Particles >6µm		ASTM D7647	>1300	<b>2386</b>	<b>4801</b>	▲ 5314
Particles >14µm		ASTM D7647	>80	<b>120</b>	<b>3</b> 74	<b>4</b> 61
Particles >21µm		ASTM D7647	>20	<b>A</b> 27	<u> </u>	<b>9</b> 5
Particles >38µm		ASTM D7647	>4	0	2	2
Particles >71µm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<b>20/18/14</b>	<b>1</b> /19/16	▲ 20/16
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.44	0.41	0.374
·52·/1) Boy: 1	3 3		-	Contact/Locatio		

Report Id: NONDAN [WUSCAR] 06061969 (Generated: 01/18/2024 12:52:41) Rev: 1

Contact/Location: Service Manager - NONDAN




## **OIL ANALYSIS REPORT**

scalar

\*Visual

NONE





NONE

NONE

NONE

Bottom

