

# **OIL ANALYSIS REPORT**

#### Area Paper Cup Machines Machine Id PMC 1003 POS-224 (S/N 1 180443 2550 4) Component

**Circulating System** 

SUMMIT Syngear SH-1032 320 (85 GAL)

# DIAGNOSIS

## Recommendation

We recommend you service the filters on this component if applicable. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

#### Wear

All component wear rates are normal.

# Contamination

There is a moderate amount of visible silt present in the sample.

# **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is acceptable for the time in service.



SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO50001943	TO50001722	TO50001694
Sample Date		Client Info		11 Jan 2024	07 Sep 2023	07 Jun 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				ABNORMAL	ABNORMAL	SEVERE
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		14	16	17
Iron	ppm	ASTM D5185m		18	11	11
Chromium	ppm	ASTM D5185m		<1	0	0
Nickel	ppm	ASTM D5185m		8	<1	0
Titanium	ppm	ASTM D5185m		<1	0	0
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m		2	0	0
Lead	ppm	ASTM D5185m		0	<1	0
Copper	ppm	ASTM D5185m		2	1	1
Tin	ppm	ASTM D5185m		<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		77	65	67
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m		<1	2	0
Calcium	ppm	ASTM D5185m		2	0	<1
Phosphorus	ppm	ASTM D5185m		648	513	519
Zinc	ppm	ASTM D5185m		0	0	0
Sulfur	ppm	ASTM D5185m		8659	7923	8482
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m		5797	4677	7170
Sodium	ppm	ASTM D5185m		4	2	<1
Potassium	ppm	ASTM D5185m	>20	<1	<1	<1
Water	%	ASTM D6304		0.015	0.009	<b>0</b> .116
ppm Water	ppm	ASTM D6304		155	96.6	<b>▲</b> 1160
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>1300		<b>4</b> 94048	▲ 52022
Particles >6µm		ASTM D7647	>320		<u> </u>	<u>▲</u> 7166
Particles >14µm		ASTM D7647	>80		<b>9</b> 3	<b>1</b> 49
Particles >21µm		ASTM D7647	>20		10	<u> </u>
Particles >38µm		ASTM D7647	>4		2	3
Particles >71µm		ASTM D7647	>3		0	0
Oil Cleanliness		ISO 4406 (c)	>17/15/13		<b>4</b> /21/14	▲ 23/20/14
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma KOH/a	ASTM D8045		0.69	0.72	0.67

Report Id: DARDALTX [WUSCAR] 06062669 (Generated: 01/20/2024 01:34:03) Rev: 1

Submitted By: YON PALOMINO



# **OIL ANALYSIS REPORT**



VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	A MODER	🔺 MODER	NONE
Debris	scalar	*Visual	NONE	NONE	🔺 MODER	🔺 MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	🔺 HAZY	NORML	A HAZY
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual		NEG	NEG	<b>(</b> 0.2%
Free Water	scalar	*Visual		NEG	NEG	<b>1</b> .0
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	326	320	313	318
Visc @ 100°C	cSt	ASTM D445	33.4	31.1	31.5	32.4
Viscosity Index (VI)	Scale	ASTM D2270	145	134	139	142
SAMPLE IMAGES	6	method	limit/base	current	history1	history2
Color						11924

Bottom

