


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id **8117061**

Component **Diesel Engine**

{not provided} (--- QTS)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

	Jan/224							
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2		
	VIZTION	Client Info	mmoasc	IL0034901				
Sample Number		Client Info		11 Jan 2024				
Sample Date	mls	Client Info		11 Jan 2024 190982				
Machine Age Oil Age	mls	Client Info		0				
Oil Changed	11115	Client Info		N/A				
Sample Status		Olletti Ittio		NORMAL				
CONTAMINATIO	N	method	limit/base	current	history1	history2		
Water		WC Method	>0.2	NEG				
Glycol		WC Method		NEG				
WEAR METALS		method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>100	5				
Chromium	ppm	ASTM D5185m	>20	<1				
Nickel	ppm	ASTM D5185m	>4	0				
Titanium	ppm	ASTM D5185m		0				
Silver	ppm	ASTM D5185m	>3	0				
Aluminum	ppm	ASTM D5185m	>20	2				
Lead	ppm	ASTM D5185m	>40	<1				
Copper	ppm	ASTM D5185m	>330	0				
Tin	ppm	ASTM D5185m	>15	<1				
Vanadium	ppm	ASTM D5185m		0				
Cadmium	ppm	ASTM D5185m		0				
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m		49				
Barium	ppm	ASTM D5185m		0				
Molybdenum	ppm	ASTM D5185m		38				
Manganese	ppm	ASTM D5185m		<1				
Magnesium	ppm	ASTM D5185m		495				
Calcium	ppm	ASTM D5185m		1517				
Phosphorus	ppm	ASTM D5185m		762				
Zinc	ppm	ASTM D5185m		865				
Sulfur	ppm	ASTM D5185m		2355				
CONTAMINANTS	8	method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>25	8				
Sodium	ppm	ASTM D5185m		2				
Potassium	ppm	ASTM D5185m	>20	3				
Fuel	%	ASTM D3524	>5	<1.0				
INFRA-RED		method	limit/base	current	history1	history2		
Soot %	%	*ASTM D7844	>3	0.1				
Nitration	Abs/cm	*ASTM D7624	>20	6.6				
Sulfation	Abs/.1mm	*ASTM D7415	>30	21.6				
FLUID DEGRADATION method limit/base current history1 history2								
Oxidation	Abs/.1mm	*ASTM D7414	>25	20.3				
Base Number (BN)	mg KOH/g	ASTM D2896		9.6				
= 1.00 · (DIV)	9			0.0				




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERTIES method limit/base current history1 history2						historv2


1 2015 1 1101 2111120					
Visc @ 100°C	cSt	ASTM D445	10.3	 	

Viscosity @ 100°C () 14 () 001) ±312











Laboratory Sample No. Lab Number **Unique Number** : 10834715

: IL0034901 : 06063333

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

Recieved : 17 Jan 2024 Diagnosed : 19 Jan 2024

Diagnostician : Don Baldridge

Test Package : FLEET (Additional Tests: FuelDilution) To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

IDEALEASE OF ATLANTA - FULTON

4675 BAKERS FERRY ROAD ATLANTA, GA US 30331

Contact: DAVID JOHNS davidjohns@idealease.com

T: (404)699-5571 F: (404)699-7420