




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
(PUN7542)
Machine Id
FREIGHTLINER 4557
Component
Diesel Engine
Fluid
DIESEL ENGINE OIL SAE 40 (--- GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			WC0847890	WC0759989	---
Sample Date	Client Info			09 Nov 2023	07 Feb 2023	---
Machine Age	hrs	Client Info		8771	6674	---
Oil Age	hrs	Client Info		6674	630	---
Oil Changed	Client Info			Changed	Changed	---
Sample Status				NORMAL	NORMAL	---

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<1.0	<1.0	---
Water	WC Method	>0.2		NEG	NEG	---
Glycol	WC Method			NEG	NEG	---

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>80	57	24	---
Chromium	ppm	ASTM D5185m	>5	2	1	---
Nickel	ppm	ASTM D5185m	>2	<1	0	---
Titanium	ppm	ASTM D5185m		0	0	---
Silver	ppm	ASTM D5185m	>3	<1	0	---
Aluminum	ppm	ASTM D5185m	>30	5	2	---
Lead	ppm	ASTM D5185m	>30	<1	0	---
Copper	ppm	ASTM D5185m	>150	3	2	---
Tin	ppm	ASTM D5185m	>5	<1	<1	---
Vanadium	ppm	ASTM D5185m		0	0	---
Cadmium	ppm	ASTM D5185m		0	0	---

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	8	4	---
Barium	ppm	ASTM D5185m	10	0	<1	---
Molybdenum	ppm	ASTM D5185m	100	64	58	---
Manganese	ppm	ASTM D5185m		<1	<1	---
Magnesium	ppm	ASTM D5185m	450	910	826	---
Calcium	ppm	ASTM D5185m	3000	1135	1201	---
Phosphorus	ppm	ASTM D5185m	1150	1097	979	---
Zinc	ppm	ASTM D5185m	1350	1282	1212	---
Sulfur	ppm	ASTM D5185m	4250	2863	3125	---



CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>20	12	6	---
Sodium	ppm	ASTM D5185m	>216	6	4	---
Potassium	ppm	ASTM D5185m	>20	5	5	---

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	1.4	0.6	---
Nitration	Abs/cm	*ASTM D7624	>20	15.0	9.9	---
Sulfation	Abs/.1mm	*ASTM D7415	>30	28.7	21.6	---

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	28.3	19.2	---
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	6.1	7.6	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	14.3	13.2	---

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0847890 **Recieved** : 17 Jan 2024
Lab Number : **06063414** **Diagnosed** : 19 Jan 2024
Unique Number : 10834796 **Diagnostician** : Don Baldrige
Test Package : CONST (Additional Tests: TBN)

Apple Valley Waste - Chambersburg District
 5436 Sunset Pike
 Chambersburg, PA
 US 17202
 Contact: BRAD DENNEN
 bandres@goldmedal.net

Certificate L2367
 To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)