

# **OIL ANALYSIS REPORT**

# Sample Rating Trend





Compressor Fluid KAESER SIGMA (OEM) S-460 (--- GAL)

#### DIAGNOSIS

## Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count on this sample.

# Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

## Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


		0ct2020	Jun2021	Feb2022 Apr2023	Jan 2024	
SAMPLE INFORM	1ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA011275	KCP52843	KCP38282
Sample Date		Client Info		02 Jan 2024	10 Apr 2023	18 Feb 2022
Machine Age	hrs	Client Info		29508	25448	19027
Oil Age	hrs	Client Info		0	6423	7700
Oil Changed		Client Info		N/A	Changed	Changed
Sample Status				NORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	<1	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	<1	0	<1
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	6	7	4
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	<1
Barium	ppm	ASTM D5185m	90	6	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		<1	<1	<1
Magnesium	ppm	ASTM D5185m	90	73	2	5
Calcium	ppm	ASTM D5185m	2	4	0	0
Phosphorus	ppm	ASTM D5185m		<1	4	14
Zinc	ppm	ASTM D5185m		4	2	3
Sulfur	ppm	ASTM D5185m		18197	20942	13338
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	0	1
Sodium	ppm	ASTM D5185m		16	<1	4
Potassium	ppm	ASTM D5185m	>20	11	<1	1
Water	%	ASTM D6304	>0.05	0.020	0.006	0.006
ppm Water	ppm	ASTM D6304	>500	201	68.0	67.7
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647			913	
Particles >6µm		ASTM D7647	>1300		336	
Particles >14µm		ASTM D7647	>80		54	
Particles >21µm		ASTM D7647	>20		23	
Particles >38µm		ASTM D7647	>4		2	
Particles >71µm		ASTM D7647	>3		0	
Oil Cleanliness		ISO 4406 (c)	>/17/13		17/16/13	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.39	0.45	0.27
5.40.40) David			<b>•</b> • • • •			


Report Id: CKSATLKCP [WUSCAR] 06064358 (Generated: 01/20/2024 05:18:19) Rev: 1


Contact/Location: GOTTLIEB GODDARD - CKSATLKCP



**OIL ANALYSIS REPORT** 







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	HEAVY	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	🔺 MODER
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPER	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	46.5	44.6	43.5
SAMPLE IMAGES		method	limit/base	current	history1	history2

Color



Bottom

