



OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Machine Id


614

Component

Diesel Engine

Fluid

PETRO CANADA TEST OIL GREY II HDEO 0W20 (--- GAL)



DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		AK0000103	AK0000108	AK0000110
Sample Date	Client Info		02 Jan 2024	18 Dec 2023	31 Oct 2023
Machine Age	mls	Client Info	624226	614079	603283
Oil Age	mls	Client Info	10147	46840	0
Oil Changed	Client Info		Not Changed	Changed	Not Changed
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >90	30	40	21
Chromium	ppm	ASTM D5185m >20	3	2	<1
Nickel	ppm	ASTM D5185m >2	0	<1	<1
Titanium	ppm	ASTM D5185m >2	0	<1	0
Silver	ppm	ASTM D5185m >2	0	0	<1
Aluminum	ppm	ASTM D5185m >20	<1	3	3
Lead	ppm	ASTM D5185m >40	<1	4	3
Copper	ppm	ASTM D5185m >330	<1	1	<1
Tin	ppm	ASTM D5185m >15	<1	<1	<1
Vanadium	ppm	ASTM D5185m	<1	0	<1
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	3
Barium	ppm	ASTM D5185m	0	9	0
Molybdenum	ppm	ASTM D5185m	60	65	62
Manganese	ppm	ASTM D5185m	<1	<1	<1
Magnesium	ppm	ASTM D5185m	1032	1004	974
Calcium	ppm	ASTM D5185m	1049	1113	1066
Phosphorus	ppm	ASTM D5185m	1117	1098	1015
Zinc	ppm	ASTM D5185m	1310	1290	1332
Sulfur	ppm	ASTM D5185m	3201	3009	2948

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	4	5	4
Sodium	ppm	ASTM D5185m	2	0	<1
Potassium	ppm	ASTM D5185m >20	<1	3	1



INFRA-RED

	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >6	0.1	0.5	0.3
Nitration	Abs/cm	*ASTM D7624 >20	6.5	10.9	9.9
Sulfation	Abs/.1mm	*ASTM D7415 >30	25.0	29.6	27.8

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	21.5	26.9	24.7
Base Number (BN)	mg KOH/g	ASTM D2896	8.8	5.2	6.3





OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	8.4	8.7	8.4

GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : AK0000103 **Received** : 18 Jan 2024
Lab Number : **06064820** **Diagnosed** : 19 Jan 2024
Unique Number : 10836202 **Diagnostician** : Wes Davis
Test Package : FLEET

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

MEYER LOGISTICS
 560 EAST 25TH ST
 JASPER, IN
 US 47546

Contact: KEN FROMME
kenny.fromme@meyerdistributing.com

T: (812)639-9224

F: