


### **OIL ANALYSIS REPORT**



<sup>Machine Id</sup> 1432799 (S/N 3612857) Component

# Compressor

### KAESER SIGMA (OEM) M-460 (--- GAL)

#### DIAGNOSIS

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFURIN	ATION	method	iinii/base	current	riistory i	nistory2
Sample Number		Client Info		KCPA006523	KCP51543	KCP35537
Sample Date		Client Info		08 Jan 2024	14 Jul 2022	26 May 2021
Machine Age	hrs	Client Info		67046	64583	59063
Oil Age	hrs	Client Info		0	3000	0
Oil Changed		Client Info		N/A	Changed	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3	2	2
Chromium	ppm	ASTM D5185m		۲ ۲	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m		۰ <1	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum		ASTM D5185m		2	<1	<1
	ppm		>10	2 <1	<1	<1
Lead	ppm	ASTM D5185m				
Copper	ppm	ASTM D5185m		1	2	<1
Tin	ppm	ASTM D5185m	>10	<1 	0	0
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	<1	18
Barium	ppm	ASTM D5185m	90	8	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	<1
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	50	5	40
Calcium	ppm	ASTM D5185m	0	1	0	0
Phosphorus	ppm	ASTM D5185m	0	27	11	<1
Zinc	ppm	ASTM D5185m	0	2	17	14
Sulfur	ppm	ASTM D5185m	23500	22062	22194	18708
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	<1
Sodium	ppm	ASTM D5185m		9	1	10
Potassium	ppm	ASTM D5185m	>20	2	0	5
Water	%	ASTM D6304	>0.05	0.018	0.006	0.023
ppm Water	ppm	ASTM D6304	>500	189	65.4	236.5
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		36089	23155	14755
Particles >6µm		ASTM D7647	>1300	<b>A</b> 2806	▲ 5985	<b>A</b> 2258
Particles >14µm		ASTM D7647	>80	40	▲ 505	<u> </u>
Particles >21µm		ASTM D7647	>20	10	<b>1</b> 13	<b>6</b> 2
Particles >38µm		ASTM D7647	>4	1	<b>1</b> 2	3
Particles >71µm		ASTM D7647	>3	0	1	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u> </u>	<u> </u>	▲ 18/15
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.37	0.44	0.377
1:54:43) Rev: 1	ing NOT I/g	A0 HVI D0040	1.0			A - DANSANC
1.34.43) NEV. 1				Contact/Loca	alon. J. PADILL	.A - DAINSAIN


Report Id: DANSANCA [WUSCAR] 06065035 (Generated: 01/22/2024 11:54:43) Rev: 1


Page 1 of 2



## **OIL ANALYSIS REPORT**







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	LIGHT	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	LIGHT
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	45	46.3	46.45	44.7
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color				a.		

Bottom

