

OIL ANALYSIS REPORT

Sample Rating Trend



40-PC-24 (S/N 64)

Hydraulic System Fluid Skydrol (--- LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Chlorine 236 ppm.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.


SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0887161		
Sample Date		Client Info		16 Jan 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0		
Chromium	ppm	ASTM D5185m	>20	9		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	2		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	<1		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		<1		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		3		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m	110	<1		
Phosphorus	ppm	ASTM D5185m	37	45327		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m	220	1640		
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>15	0		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	14		
Chlorine Content	ppm	ASTM D5185m		236		
Water	%	ASTM D6304		0.541		
ppm Water	ppm	ASTM D6304	>7500	5410		
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>5000	693		
Particles >6µm		ASTM D7647		216		
Particles >14µm		ASTM D7647	>160	18		
Particles >21µm		ASTM D7647		7		
Particles >38µm		ASTM D7647	>10	1		
Particles >71µm		ASTM D7647		0		
Oil Cleanliness		ISO 4406 (c)	>19/17/14	17/15/11		
FLUID DEGRAD		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.04	0.114		


Report Id: WOOSANCA [WUSCAR] 06065250 (Generated: 02/08/2024 17:42:18) Rev: 1


Contact/Location: REYNARD GOLDMAN - WOOSANCA



OIL ANALYSIS REPORT







* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: REYNARD GOLDMAN - WOOSANCA

F:

T: (661)702-5991