

OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id

39-PC-24 (S/N 60C) Component Hydraulic System Fluid Skydrol (--- LTR)

DIAGNOSIS

Recommendation

We advise that you perform a filter service, and use off-line filtration to improve the cleanliness of the system fluid. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles and water present in this sample. Chlorine 304 ppm.

Wear

All component wear rates are normal.

Contamination

Moderate concentration of visible dirt/debris present in the oil. There is a moderate concentration of water present in the oil.


Fluid Condition


The AN level is acceptable for this fluid.


SAMPLE INFORM	ATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0887160		
Sample Date		Client Info		16 Jan 2024		
Machine Age	hrs	Client Info		0		
Oil Age	hrs	Client Info		0		
Oil Changed		Client Info		N/A		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>20	0		
Chromium	ppm	ASTM D5185m	>20	9		
Nickel	ppm	ASTM D5185m	>20	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>20	2		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m	>20	<1		
Tin	ppm	ASTM D5185m	>20	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
ADDITIVES Boron	ppm	method ASTM D5185m	limit/base	current 6	history1	history2
	ppm ppm		limit/base			
Boron		ASTM D5185m	limit/base	6		
Boron Barium	ppm	ASTM D5185m ASTM D5185m	limit/base	6 0		
Boron Barium Molybdenum	ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	6 0 0		
Boron Barium Molybdenum Manganese	ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base	6 0 0 0		
Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m		6 0 0 <1		
Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	110	6 0 0 <1 2	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	110	6 0 0 <1 2 47480	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	110 37	6 0 0 <1 2 47480 0	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	110 37 220	6 0 0 <1 2 47480 0 1780	 	
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	110 37 220 limit/base	6 0 0 <1 2 47480 0 1780 current	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method	110 37 220 limit/base	6 0 0 <1 2 47480 0 1780 current 0	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	110 37 220 Iimit/base >15	6 0 0 <1 2 47480 0 1780 current 0 0	history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	110 37 220 Iimit/base >15	6 0 0 <1 2 47480 0 1780 <u>current</u> 0 0 13	 history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Chlorine Content	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	110 37 220 limit/base >15 >20	6 0 0 2 1 2 47480 0 1780 <u>current</u> 0 0 13 304	history1	 history2
Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium Chlorine Content Water	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	110 37 220 limit/base >15 >20 >20 >15	6 0 0 2 4 1 2 47480 0 1780 0 1780 0 0 1780 0 13 304 ▲ 0.786	history1	 history2



OIL ANALYSIS REPORT







	VISUAL		method	limit/base	e current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
1	Debris	scalar	*Visual	NONE	🔺 MODER		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Jan 16/24	Appearance	scalar	*Visual	NORML	NORML		
Jan	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.750	0.2%		
	Free Water	scalar	*Visual		NEG		
	FLUID PROPERT	TIES	method	limit/base	e current	history1	history2
	Visc @ 40°C	cSt	ASTM D445	10.55	7.57		
	SAMPLE IMAGES	S	method	limit/base	e current	history1	history2
Jan16/24	Color				a .	no image	no image
	Bottom					no image	no image
	Non-ferrous Metal	s		Jan 16/24			
	ued 4			/24			
	Viscosity @ 40°C			Jan16/24			
	14 _T			_1	Acid Number		
	12 - Abnormal			KOH	Abnormal		
	(2) (2) (4) (4) (1) (2) (2) (2) (3) (4) (4) (4) (4) (4) (4) (4) (4) (4) (4			Acid Number (mg KOH(g)	1.72 -		
				0 mp	.48		
	Abnormal			O N	.24 Base		
	6440			24 +			****
	Jan 16,24			Jan 16/24	Jan 16/24		
		1 Madiaa	on Ave., Cary				WOODWAR

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: REYNARD GOLDMAN - WOOSANCA

F: