

## **OIL ANALYSIS REPORT**

• Sar

Sample Rating Trend

WEAR



Machine Id

# KAESER AS 20 5679874 (S/N 1152)

Component

Compressor

KAESER SIGMA (OEM) FG-460 (--- QTS)

### DIAGNOSIS

#### Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

## Wear

The aluminum level has decreased, but is still abnormal. All other component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Aug <sup>2</sup> 022	Sep2023		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP40060D	KCP48297	
Sample Date		Client Info		13 Sep 2023	21 Aug 2022	
Machine Age	hrs	Client Info		23014	21477	
Oil Age	hrs	Client Info		0	300	
Oil Changed		Client Info		Changed	Changed	
Sample Status				ABNORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	16	<b>▲</b> 56	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	<1	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	<u> 16</u>	<b>△</b> 23	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>50	2	3	
Tin	ppm	ASTM D5185m	>10	0	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m		0	0	
Molybdenum	ppm	ASTM D5185m		0	<1	
Manganese	ppm	ASTM D5185m		0	0	
Magnesium	ppm	ASTM D5185m		0	0	
Calcium	ppm	ASTM D5185m		0	0	
Phosphorus	ppm	ASTM D5185m	500	427	506	
Zinc	ppm	ASTM D5185m		472	236	
Sulfur	ppm	ASTM D5185m		1589	2183	
CONTAMINANTS	}	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	
Sodium	ppm	ASTM D5185m		2	<1	
Potassium	ppm	ASTM D5185m	>20	0	0	
Water	%	ASTM D6304	>0.05	0.006	0.012	
ppm Water	ppm	ASTM D6304	>500	62	120.1	
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		1394	12354	
Particles >6µm		ASTM D7647	>1300	398	<u>△</u> 2540	
Particles >14µm		ASTM D7647	>80	28	<u>▲</u> 273	
Particles >21µm		ASTM D7647	>20	7	▲ 80	
Particles >38μm		ASTM D7647	>4	0	<u> </u>	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	18/16/12	<u>\$\text{\Delta}\$ 21/19/15</u>	
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.5	1.05	1.11	

Contact/Location: BRAD ? - RIVMAN



## **OIL ANALYSIS REPORT**



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: