


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id 1640 Component

Transmission (Auto)

TRANS CREST (--- GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the fluid.


Fluid Condition

The condition of the fluid is acceptable for the time in service.


| | | | | Jan2024 | | |
|-------------------|--------|-------------|------------|-------------|----------|----------|
| 0.41401 5 1115001 | | | | | | |
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | WC0858184 | | |
| Sample Date | | Client Info | | 24 Jan 2024 | | |
| Machine Age | hrs | Client Info | | 12064 | | |
| Oil Age | hrs | Client Info | | 3300 | | |
| Oil Changed | | Client Info | | Changed | | |
| Sample Status | | | | NORMAL | | |
| CONTAMINATION | ٧ | method | limit/base | current | history1 | history2 |
| Water | | WC Method | >0.1 | NEG | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >160 | 51 | | |
| Chromium | ppm | ASTM D5185m | >5 | 0 | | |
| Nickel | ppm | ASTM D5185m | >5 | <1 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | >5 | 0 | | |
| Aluminum | ppm | ASTM D5185m | >50 | 19 | | |
| Lead | ppm | ASTM D5185m | >50 | 4 | | |
| Copper | ppm | ASTM D5185m | >225 | 17 | | |
| Tin | ppm | ASTM D5185m | >10 | 2 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| | PP | | | | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 113 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | <1 | | |
| Magnesium | ppm | ASTM D5185m | | 3 | | |
| Calcium | ppm | ASTM D5185m | | 134 | | |
| Phosphorus | ppm | ASTM D5185m | | 280 | | |
| Zinc | ppm | ASTM D5185m | | 3 | | |
| Sulfur | ppm | ASTM D5185m | | 1437 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >20 | 4 | | |
| Sodium | ppm | ASTM D5185m | | 4 | | |
| Potassium | ppm | ASTM D5185m | >20 | <1 | | |
| VISUAL | | method | limit/base | current | history1 | history2 |
| White Metal | scalar | *Visual | NONE | NONE | | |
| Yellow Metal | scalar | *Visual | NONE | NONE | | |
| Precipitate | scalar | *Visual | NONE | NONE | | |
| Silt | scalar | *Visual | NONE | NONE | | |
| Debris | scalar | *Visual | NONE | LIGHT | | |
| Sand/Dirt | scalar | *Visual | NONE | NONE | | |
| Appearance | scalar | *Visual | NORML | NORML | | |
| Odor | scalar | *Visual | NORML | NORML | | |
| Emulsified Water | scalar | *Visual | >0.1 | NEG | | |
| Free Water | scalar | *Visual | | NEG | | |
| | | | | | | |




OIL ANALYSIS REPORT



| FLUID PROPERTIES | | method | limit/base | current | history1 | history2 |
|------------------|-----|-----------|------------|----------|----------|----------|
| Visc @ 40°C | cSt | ASTM D445 | | 34.9 | | |
| SAMPLE IMAGES | | method | limit/base | current | history1 | history2 |
| Color | | | | no image | no image | no image |
| Bottom | | | | no image | no image | no image |













Certificate L2367

Laboratory Sample No. Lab Number

Unique Number : 10856341

: WC0858184 : 06074250 Test Package : CONST

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Recieved : 30 Jan 2024 Diagnosed : 31 Jan 2024 Diagnostician : Don Baldridge

Apple Valley Waste - Hometown Location 155 Airport Road

Selinsgrove, PA US 17870

Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: