


OIL ANALYSIS REPORT

GUAY SON [CONHER] **MADE IN MEXICO IBACO BM NAUTICO 4**

Component

Transmission (Manual)

RALOY SAE 50 (60 LTR)





DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the fluid.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the fluid is suitable for further service.

		Mar2022	Oct2022 Mar2023	Sep 2023 Oct 2023	Jan 2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KL0013476	KL0013341	KL0012837
Sample Date		Client Info		20 Jan 2024	25 Oct 2023	20 Sep 2023
Machine Age	hrs	Client Info		18256	17040	16363
Oil Age	hrs	Client Info		1896	680	555
Oil Changed		Client Info		Changed	Not Changd	Not Changd
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
CONTAMINATIO	V	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	102	24	13
Chromium	ppm	ASTM D5185m	>5	<1	0	0
Nickel	ppm	ASTM D5185m	>5	<1	0	0
Titanium	ppm	ASTM D5185m		<1	<1	0
Silver	ppm	ASTM D5185m	>7	0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	<1	<1
Lead	ppm	ASTM D5185m	>45	7	5	7
Copper	ppm	ASTM D5185m	>225	39	7	9
Tin	ppm	ASTM D5185m	>10	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	<1	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m		0	0	<1
Molybdenum	ppm	ASTM D5185m		<1	<1	0
Manganese	ppm	ASTM D5185m		1	<1	<1
Magnesium	ppm	ASTM D5185m		7	8	10
Calcium	ppm	ASTM D5185m		2946	3167	3552
Phosphorus	ppm	ASTM D5185m		886	921	1027
Zinc	ppm	ASTM D5185m		852	773	858
Sulfur	ppm	ASTM D5185m		6327	5852	5774
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>125	16	9	9
Sodium	ppm	ASTM D5185m		2	2	2
Potassium	ppm	ASTM D5185m	>20	3	2	0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		113031	109589	107050
Particles >6µm		ASTM D7647	>2500	<u> </u>	<u>^</u> 24303	<u>^</u> 29751
Particles >14µm		ASTM D7647	>320	157	▲ 796	<u>495</u>
Particles >21µm		ASTM D7647	>80	33	<u>▲</u> 165	48
Particles >38μm		ASTM D7647	>20	1	2	4
Particles >71μm		ASTM D7647		0	0	2
Oil Cleanliness		ISO 4406 (c)	>18/15	<u>^</u> 21/14	<u>^</u> 22/17	△ 22/16
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045

0.88

0.83

0.70



OIL ANALYSIS REPORT







Certificate L2367

Laboratory Sample No. Lab Number **Unique Number**

: KL0013476 : 06074659 : 10856750

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : 30 Jan 2024 Recieved Diagnosed : 01 Feb 2024 Diagnostician : Don Baldridge

Test Package : MOB 2 (Additional Tests: PrtCount)

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

CONOR JUAREZ 348 HERMOSILLO. MX 83140

Contact: EDUARDO GARCIA egarcia.comsa@gmail.com

T: (526)622-1581 x:81 F: x:

Submitted By: EDUARDO GARCIA