

# **OIL ANALYSIS REPORT**

#### Area ULTRA COOLANT Machine Id INGERSOLL RAND CBV553186 - PERMOBIL Component

Compressor

#### DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

## Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil.

# Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



Sample Rating Trend




NORMAL


SAMPLE INFORM	<b>NATION</b>	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06074868		
Sample Date		Client Info		24 Jan 2024		
Machine Age	hrs	Client Info		49929		
Oil Age	hrs	Client Info		2034		
Oil Changed		Client Info		Not Changd		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		<1		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	<1		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	0		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m	556	900		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		1		
Calcium	ppm	ASTM D5185m	242	4		
Phosphorus	ppm	ASTM D5185m	0	0		
Zinc	ppm	ASTM D5185m	0	27		
Sulfur	ppm	ASTM D5185m	306	335		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		14		
Potassium	ppm	ASTM D5185m	>20	1		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.2	0.094		



# **OIL ANALYSIS REPORT**

VISUAL





Laboratory	: We	: UCH06074868 Recieved : 30 Jan 2024   : 06074868 Diagnosed : 01 Feb 2024   : 10856959 Diagnostician : Don Baldridge						HENRY FOSTER COMPANY 4700 LEBOURGET STREET SAINT LOUIS, MO US 63134 htact: RACHEL VON HATTEN rvonhatten@jhf.com T: (314)593-1267		
	cst (40°C) cst (4	iscosity @ 40° ubnormal lase ubnormal			42/42/4 90.02 90.0 Mumber (mg K0H/6) 90.0 Participation (mg K0H/6) 90.0 Participation (mg K0H/6) 90.0 Participation (mg K0H/6)	Acid Number		24		
	0 +72/h2uer N 10	on-ferrous Me	als		Jan24/24					
		iron hromium nickel								
	Bot	lor ttom					no image no image	no image no image		
	S	c @ 40°C AMPLE IMAG	cSt ES	ASTM D445 method	52 limit/base	51.6 current	history1	history2		
		LUID PROPEI		method	limit/base	current	history1	history2		
:	Em	ulsified Water e Water	scalar scalar	*Visual *Visual	>0.1	NEG				
100 PC		pearance	scalar	*Visual *Visual	NORML	NORML				
	Deb Sar	bris nd/Dirt	scalar scalar	*Visual *Visual	NONE	NONE NONE				
	Pre Silt	ecipitate	scalar scalar	*Visual *Visual	NONE NONE	NONE NONE				
			scalar		NONE	NONE				

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)