

OIL ANALYSIS REPORT

Area OKLAHOMA/102/EG - DOZER Machine Id 35.101L [OKLAHOMA^102^EG - DOZER] Component

Diesel Engine

MOBIL DELVAC 1300 SUPER15W40 (--- GAL)





DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Fluid

🔺 Wear

An increase in the iron level is noted. All other component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0873895	WC0857351	WC0819874
Sample Date		Client Info		11 Jan 2024	17 Oct 2023	17 Jul 2023
Machine Age	hrs	Client Info		12101	8898	8667
Oil Age	hrs	Client Info		250	6708	6477
Oil Changed		Client Info		Changed	Changed	N/A
Sample Status				ATTENTION	NORMAL	NORMAL
CONTAMINATION	٧	method	limit/base	current	history1	history2
Fuel		WC Method	\ 5	~10	<1.0	<1.0
Water		WC Method	>0.2	NEG	NEG	NEG
Glycol		WC Method	20.L	NEG	NEG	NEG
				NEG	historud	history
WEAR METALS		method	limit/base	current	nistory i	nistory2
Iron	ppm	ASTM D5185m	>100	8 5	12	16
Chromium	ppm	ASTM D5185m	>20	3	<1	<1
Nickel	ppm	ASTM D5185m	>2	1	<1	0
Titanium	ppm	ASTM D5185m	>2	<1	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>25	7	3	6
Lead	ppm	ASTM D5185m	>40	16	<1	0
Copper	ppm	ASTM D5185m	>330	30	<1	<1
Tin	ppm	ASTM D5185m	>15	2	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
Cadmium ADDITIVES	ppm	ASTM D5185m method	limit/base	0 current	0 history1	0 history2
Cadmium ADDITIVES Boron	ppm ppm	ASTM D5185m method ASTM D5185m	limit/base 0	0 current 48	0 history1 40	0 history2 38
Cadmium ADDITIVES Boron Barium	ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m	limit/base 0 0	0 current 48 <1	0 history1 40 0	0 history2 38 0
Cadmium ADDITIVES Boron Barium Molybdenum	ppm ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0	0 current 48 <1 49	0 history1 40 0 45	0 history2 38 0 44
Cadmium ADDITIVES Boron Barium Molybdenum Manganese	ppm ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0	0 current 48 <1 49 <1	0 history1 40 0 45 0	0 history2 38 0 44 <1
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium	ppm ppm ppm ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0	0 current 48 <1 49 <1 535	0 history1 40 0 45 0 511	0 history2 38 0 44 <1 566
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium	ppm ppm ppm ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0	0 current 48 <1 49 <1 535 1788	0 history1 40 0 45 0 511 1644	0 history2 38 0 44 <1 566 1782
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus	ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0	0 current 48 <1 49 <1 535 1788 795	0 history1 40 0 45 0 511 1644 771	0 history2 38 0 44 <1 566 1782 757
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc	ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m Method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0	0 current 48 <1 49 <1 535 1788 795 944	0 history1 40 0 45 0 511 1644 771 920	0 history2 38 0 44 <1 566 1782 757 977
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m Method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0	0 current 48 <1 49 <1 535 1788 795 944 2279	0 history1 40 0 45 0 511 1644 771 920 2870	0 history2 38 0 44 <1 566 1782 757 977 2940
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS	ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 0 1 0 1 1 1 1 1 1 1 1 1 1 1	0 current 48 <1 49 <1 535 1788 795 944 2279 current	0 history1 40 0 45 0 511 1644 771 920 2870 history1	0 history2 38 0 44 <1 566 1782 757 977 2940 history2
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18	0 history1 40 0 45 0 511 1644 771 920 2870 2870 history1 5	0 history2 38 0 44 <1 566 1782 757 977 2940 history2 5
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium	ppm // pp	ASTM D5185m Method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6	0 history1 40 0 45 0 511 1644 771 920 2870 2870 history1 5 4	0 history2 38 0 44 <1 566 1782 757 977 2977 2940 history2 5 8
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m ASTM D5185m method ASTM D5185m ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4	0 history1 40 0 45 0 511 1644 771 920 2870 2870 history1 5 4 2	0 history2 38 0 44 <1 566 1782 757 977 2940 history2 5 8 8 1
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m Method ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 0 1 0 1 0 1 0 1 0 1 0 1	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current	0 history1 40 0 45 0 511 1644 771 920 2870 2870 history1 5 4 2 2	0 history2 38 0 44 <1 566 1782 757 977 2940 history2 5 8 1 1
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot %	ppm ppm	ASTM D5185m Method ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current 1.3	0 history1 40 0 45 0 511 1644 771 920 2870 bistory1 5 4 2 2 history1 0.2	0 history2 38 0 44 <1 566 1782 757 977 2940 history2 5 8 1 1 history2 0.4
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current 1.3 12.9	0 history1 40 0 45 0 511 1644 771 920 2870 bistory1 5 4 2 2 history1 0.2 6.7	0 history2 38 0 44 <1 566 1782 757 977 2940 history2 5 8 1 1 history2 0.4 8.1
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m Method ASTM D5185m ASTM D5185m	limit/base 0 0 0 0 0 0 0 0 1 1 2 2 1 1 20 1 20	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current 1.3 12.9 28.9	0 history1 40 0 45 0 511 1644 771 920 2870 2870 history1 5 4 2 2 history1 0.2 6.7 21.0	0 history2 38 0 44 <1 566 1782 757 977 2940 bistory2 5 8 1 1 bistory2 0.4 8.1 22.4
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m ASTM	limit/base 0 <t< th=""><th>0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current 1.3 12.9 28.9 current</th><th>0 history1 40 0 511 1644 771 920 2870 history1 5 4 2 2 history1 0.2 6.7 21.0</th><th>0 history2 38 0 44 <1 566 1782 757 977 2940 bistory2 5 8 1 history2 0.4 8.1 22.4 history2</th></t<>	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current 1.3 12.9 28.9 current	0 history1 40 0 511 1644 771 920 2870 history1 5 4 2 2 history1 0.2 6.7 21.0	0 history2 38 0 44 <1 566 1782 757 977 2940 bistory2 5 8 1 history2 0.4 8.1 22.4 history2
Cadmium ADDITIVES Boron Barium Molybdenum Manganese Magnesium Calcium Phosphorus Zinc Sulfur CONTAMINANTS Silicon Sodium Potassium INFRA-RED Soot % Nitration Sulfation FLUID DEGRADA Oxidation	ppm ppm ppm ppm ppm ppm ppm ppm ppm ppm	ASTM D5185m Method ASTM D5185m ASTM D7844 *ASTM D7844 *ASTM D7415	limit/base 0 <t< th=""><th>0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current 1.3 12.9 28.9 current 30.9</th><th>0 history1 40 0 45 0 511 1644 771 920 2870 2870 history1 5 4 2 2 history1 0.2 6.7 21.0 history1 19.1</th><th>0 history2 38 0 44 <1 566 1782 757 977 2940 history2 5 8 1 history2 0.4 8.1 22.4 history2 20.3</th></t<>	0 current 48 <1 49 <1 535 1788 795 944 2279 current 18 6 4 current 1.3 12.9 28.9 current 30.9	0 history1 40 0 45 0 511 1644 771 920 2870 2870 history1 5 4 2 2 history1 0.2 6.7 21.0 history1 19.1	0 history2 38 0 44 <1 566 1782 757 977 2940 history2 5 8 1 history2 0.4 8.1 22.4 history2 20.3



Ba

Nov12/16

Jec13/18

eh28/20 Drt6/20

OIL ANALYSIS REPORT





Aug17/22

VISUAL		method				history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	14	14.1	13.3	13.4

GRAPHS Ferrous Alloys



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Certificate L2367

Submitted By: PATRICIA BIBLE

F: x: