


OIL ANALYSIS REPORT



Paper Cup Machines PMC 1003 POS-437 (S/N 199302)

Circulating System

SUMMIT Syngear SH-1032 320 (85 GAL)

DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Aug2022 N	lov2022 Dec2022 Mar20	23 Oct2023 Nov2023 Jan2024	Jan 2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO50002014	TO50001951	TO50001972
Sample Date		Client Info		29 Jan 2024	21 Jan 2024	16 Nov 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
PQ		ASTM D8184		16	17	16
Iron	ppm	ASTM D5185m		8	3	11
Chromium	ppm	ASTM D5185m		0	0	<1
Nickel	ppm	ASTM D5185m		7	0	6
Titanium	ppm	ASTM D5185m		<1	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m		<1	0	2
Lead	ppm	ASTM D5185m		<1	0	<1
Copper	ppm	ASTM D5185m		2	3	2
Tin	ppm	ASTM D5185m		<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		87	68	91
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	<1
Manganese	ppm	ASTM D5185m		<1	1	<1
Magnesium	ppm	ASTM D5185m		0	<1	<1
Calcium	ppm	ASTM D5185m		0	45	4
Phosphorus	ppm	ASTM D5185m		492	438	493
Zinc	ppm	ASTM D5185m		0	8	0
Sulfur	ppm	ASTM D5185m		7254	6126	8085
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m		3954	3421	4454
Sodium	ppm	ASTM D5185m		1	0	<1
Potassium	ppm	ASTM D5185m	>20	0	0	1
Water	%	ASTM D6304		0.017	0.021	0.018
ppm Water	ppm	ASTM D6304		176	216	180
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>1300	<u> </u>	<u>44518</u>	
Particles >6µm		ASTM D7647	>320	<u> </u>	△ 3795	
Particles >14μm		ASTM D7647	>80	<u> </u>	60	
Particles >21μm		ASTM D7647	>20	<u>^</u> 60	12	
Particles >38μm		ASTM D7647	>4	<u> </u>	1	
Particles >71μm		ASTM D7647	>3	1	0	
Oil Cleanliness		ISO 4406 (c)	>17/15/13	18/17/15	<u>\$\text{23}\19\13\$</u>	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
· · · · · · · · · · · · · · · · · · ·						

0.94

0.73



OIL ANALYSIS REPORT

