




# OIL ANALYSIS REPORT

Sample Rating Trend



**NORMAL**



Machine Id  
**MILTK49**

Component  
**Diesel Engine**

Fluid  
**DIESEL ENGINE OIL SAE 40 (--- GAL)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample. Please specify the brand, type, and viscosity of the oil on your next sample.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the oil.

### Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION		method	limit/base	current	history1	history2
Sample Number	Client Info			<b>SBP0006196</b>	SBP0006226	SBP0002350
Sample Date	Client Info			<b>12 Jan 2024</b>	17 Oct 2023	30 Aug 2023
Machine Age	hrs	Client Info		<b>350</b>	0	0
Oil Age	hrs	Client Info		<b>350</b>	0	0
Oil Changed	Client Info			<b>Not Chngd</b>	N/A	Not Chngd
Sample Status				<b>NORMAL</b>	NORMAL	ABNORMAL

CONTAMINATION		method	limit/base	current	history1	history2
Fuel	WC Method	>5		<b>&lt;1.0</b>	<1.0	0.5
Water	WC Method	>0.2		<b>NEG</b>	NEG	NEG
Glycol	WC Method			<b>NEG</b>	NEG	NEG

WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>100	<b>11</b>	17	38
Chromium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	<1	<1
Nickel	ppm	ASTM D5185m	>4	<b>&lt;1</b>	<1	<1
Titanium	ppm	ASTM D5185m		<b>&lt;1</b>	<1	<1
Silver	ppm	ASTM D5185m	>3	<b>0</b>	0	<1
Aluminum	ppm	ASTM D5185m	>20	<b>4</b>	8	▲ 27
Lead	ppm	ASTM D5185m	>40	<b>2</b>	1	<1
Copper	ppm	ASTM D5185m	>330	<b>2</b>	5	12
Tin	ppm	ASTM D5185m	>15	<b>1</b>	<1	2
Vanadium	ppm	ASTM D5185m		<b>0</b>	0	<1
Cadmium	ppm	ASTM D5185m		<b>0</b>	<1	0

ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	250	<b>1</b>	7	114
Barium	ppm	ASTM D5185m	10	<b>0</b>	3	0
Molybdenum	ppm	ASTM D5185m	100	<b>60</b>	60	11
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1	4
Magnesium	ppm	ASTM D5185m	450	<b>903</b>	931	757
Calcium	ppm	ASTM D5185m	3000	<b>990</b>	1143	1381
Phosphorus	ppm	ASTM D5185m	1150	<b>1010</b>	997	725
Zinc	ppm	ASTM D5185m	1350	<b>1160</b>	1234	828
Sulfur	ppm	ASTM D5185m	4250	<b>2908</b>	3552	3533



CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<b>5</b>	12	▲ 43
Sodium	ppm	ASTM D5185m	>216	<b>2</b>	0	5
Potassium	ppm	ASTM D5185m	>20	<b>8</b>	28	85

INFRA-RED		method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844	>3	<b>0.3</b>	0.3	0.1
Nitration	Abs/cm	*ASTM D7624	>20	<b>6.8</b>	6.7	7.5
Sulfation	Abs/.1mm	*ASTM D7415	>30	<b>18.4</b>	18.3	17.0

FLUID DEGRADATION		method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414	>25	<b>13.8</b>	13.8	11.9
Base Number (BN)	mg KOH/g	ASTM D2896	8.5	<b>8.1</b>	8.4	8.2







# OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	<b>13.5</b>	13.6	11.5

### GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : SBP0006196 **Recieved** : 01 Feb 2024  
**Lab Number** : **06077384** **Diagnosed** : 02 Feb 2024  
**Unique Number** : 10859475 **Diagnostician** : Wes Davis  
**Test Package** : FLEET

**Pillen Family Farms - 722828**  
 26741 NE-91  
 Humphrey, NE  
 US 61357  
 Contact: Troy Runge  
 troyfr@pillenfamilyparks.com  
 T: (308)390-6733  
 F:

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)