

## **OIL ANALYSIS REPORT**


PNEUTECH S-46 [275464] **INGERSOLL RAND PX8020U06325** 

Component

Compressor

{not provided} (2 GAL)

condition of the oil is suitable for further service.



Sample Rating Trend



DIAGNOSIS	SAMPLE INFORM	MATION	method	limit/base	current	ا
Recommendation	Sample Number		Client Info		UFD0000257	
Resample at the next service interval to monitor.  Wear	Sample Date Machine Age	hrs	Client Info		22 Jan 2024 80139	
All component wear rates are normal.	Oil Age	hrs	Client Info		139	
<b>Contamination</b> There is no indication of any contamination in the	Oil Changed Sample Status		Client Info		Changed NORMAL	
oil.	CONTAMINATION	V	method	limit/base	current	
Fluid Condition The AN level is acceptable for this fluid. The	Water		WC Method	>0.1	NEG	

Sodium

Potassium

FLUID DEGRADATION

Acid Number (AN)

ppm ASTM D5185m

mg KOH/g ASTM D8045

ASTM D5185m >20

ppm

Machine Age	hrs	Client Info		139		
Oil Age	IIIS	Client Info				
Oil Changed		Client into		Changed NORMAL		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	1		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		0		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		296		
Zinc	ppm	ASTM D5185m		5		
Sulfur	ppm	ASTM D5185m		41		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0		


0

<1

0.19



## **OIL ANALYSIS REPORT**




VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
<b>Emulsified Water</b>	scalar	*Visual	>0.1	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	TIES	method	limit/base	current	history1	history2

SAMPLE IMAGES	me	ethod	limit/base	current	history1	history2
Color					no image	no image
Bottom					no image	no image

43.8


## **GRAPHS**


Visc @ 40°C




cSt

ASTM D445









Certificate L2367

Laboratory Sample No.

: UFD0000257 Lab Number : 06097172 Unique Number : 10890025 Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received Tested

Diagnosed

: 23 Feb 2024

: 22 Feb 2024

: 24 Feb 2024 - Don Baldridge

**FLUID-AIRE DYNAMICS** 550 ALBION AVE SCHAUMBURG, IL US 60193

Contact: ED DIENER

To discuss this sample report, contact Customer Service at 1-800-237-1369.

ed.diener@fluidairedynamics.com T: (847)678-8388

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: