


# **OIL ANALYSIS REPORT**



ISO



# Machine Id KAESER 6439383 (S/N 1192)

Component

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		, <u> </u>	Sep2023	Feb2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA011755	KCPA004987	
Sample Date		Client Info		05 Feb 2024	19 Sep 2023	
Machine Age	hrs	Client Info		16327	14722	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	N/A	
Sample Status				ATTENTION	ATTENTION	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	<1	0	
Nickel	ppm	ASTM D5185m	>3	0	0	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	<1	0	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>50	3	5	
Tin	ppm	ASTM D5185m	>10	0	<1	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	
Barium	ppm	ASTM D5185m	90	24	8	
Molybdenum	ppm	ASTM D5185m	0	0	<1	
Manganese	ppm	ASTM D5185m		0	<1	
Magnesium	ppm	ASTM D5185m	100	47	50	
Calcium	ppm	ASTM D5185m	0	3	3	
Phosphorus	ppm	ASTM D5185m	0	<1	4	
Zinc	ppm	ASTM D5185m	0	2	2	
Sulfur	ppm	ASTM D5185m	23500	18725	24391	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	2	
Sodium	ppm	ASTM D5185m		26	22	
Potassium	ppm	ASTM D5185m	>20	5	5	
Water	%	ASTM D6304	>0.05	0.017	0.015	
ppm Water	ppm	ASTM D6304	>500	175	156.3	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		7383	6219	
Particles >6µm		ASTM D7647	>1300	<b>1446</b>	<b>1632</b>	
Particles >14μm		ASTM D7647	>80	60	<b>128</b>	
Particles >21µm		ASTM D7647	>20	13	<b>A</b> 37	
Particles >38μm		ASTM D7647	>4	0	2	
Particles >71µm		ASTM D7647	>3	0	1	
Oil Cleanliness		ISO 4406 (c)	>/17/13	<b>20/18/13</b>	<b>2</b> 0/18/14	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
A 1151 / (550)	1/011:	10T11 D06 :-	4.0			

Acid Number (AN)

mg KOH/g ASTM D8045 1.0

0.37

0.39



## **OIL ANALYSIS REPORT**

