




# OIL ANALYSIS REPORT

Sample Rating Trend

**NORMAL**



Area  
**FOUR MILE RIDGE [200005315]**  
 Machine Id  
**83304 SITE 11**  
 Component  
**Wind Turbine Gearbox**  
 Fluid  
**CASTROL OPTIGEAR SYNTHETIC X 320 (--- LTR)**

## DIAGNOSIS

### Recommendation

Resample at the next service interval to monitor.

### Wear

All component wear rates are normal.

### Contamination

There is no indication of any contamination in the component. The amount and size of particulates present in the system is acceptable.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

## SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		<b>NX012355</b>	NX004195	NX010442
Sample Date	Client Info		<b>30 Nov 2023</b>	03 Apr 2023	29 Nov 2022
Machine Age	hrs	Client Info	<b>63688</b>	57387	54782
Oil Age	hrs	Client Info	<b>63688</b>	57387	54782
Oil Changed	Client Info		<b>Not Changed</b>	Not Changd	Not Changed
Sample Status			<b>NORMAL</b>	NORMAL	NORMAL

## WEAR METALS

	method	limit/base	current	history1	history2
PQ	ASTM D8184	>80	<b>20</b>	9	11
Iron	ppm	ASTM D5185m	>150	<b>13</b>	13
Chromium	ppm	ASTM D5185m	>5	<b>0</b>	0
Nickel	ppm	ASTM D5185m	>10	<b>0</b>	0
Titanium	ppm	ASTM D5185m	>10	<b>0</b>	0
Silver	ppm	ASTM D5185m		<b>0</b>	0
Aluminum	ppm	ASTM D5185m	>10	<b>6</b>	<1
Lead	ppm	ASTM D5185m	>20	<b>0</b>	0
Copper	ppm	ASTM D5185m	>50	<b>1</b>	<1
Tin	ppm	ASTM D5185m	>10	<b>&lt;1</b>	0
Vanadium	ppm	ASTM D5185m		<b>&lt;1</b>	<1
Cadmium	ppm	ASTM D5185m		<b>0</b>	0

## ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<b>26</b>	0
Barium	ppm	ASTM D5185m		<b>2</b>	0
Molybdenum	ppm	ASTM D5185m	1150	<b>711</b>	724
Manganese	ppm	ASTM D5185m		<b>&lt;1</b>	<1
Magnesium	ppm	ASTM D5185m		<b>7</b>	10
Calcium	ppm	ASTM D5185m	2000	<b>1407</b>	1441
Phosphorus	ppm	ASTM D5185m	400	<b>331</b>	299
Zinc	ppm	ASTM D5185m	0	<b>0</b>	0
Sulfur	ppm	ASTM D5185m	1850	<b>1767</b>	1506

## CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	<b>9</b>	10
Sodium	ppm	ASTM D5185m	>20	<b>8</b>	7
Potassium	ppm	ASTM D5185m	>20	<b>&lt;1</b>	0
Water	%	ASTM D6304	>0.05	<b>0.014</b>	0.015
ppm Water	ppm	ASTM D6304	>500	<b>146</b>	155.1

## FLUID CLEANLINESS






	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647		<b>1421</b>	1176	116
Particles >6µm	ASTM D7647	>2500	<b>412</b>	351	39
Particles >14µm	ASTM D7647	>320	<b>71</b>	27	4
Particles >21µm	ASTM D7647	>80	<b>34</b>	8	1
Particles >38µm	ASTM D7647	>20	<b>3</b>	0	0
Particles >71µm	ASTM D7647	>4	<b>0</b>	0	0
Oil Cleanliness	ISO 4406 (c)	>--/18/15	<b>18/16/13</b>	17/16/12	14/12/9

## FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.6	<b>0.44</b>	0.63




# OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	320	319	314

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



## GRAPHS



**Laboratory** : WearCheck USA - 501 Madison Ave., Cary, NC 27513  
**Sample No.** : NX012355 **Received** : 22 Feb 2024  
**Lab Number** : 06097715 **Tested** : 23 Feb 2024  
**Unique Number** : 10890568 **Diagnosed** : 25 Feb 2024 - Doug Bogart  
**Test Package** : IND 2 ( Additional Tests: KF, PQ, PrtCount )

**NORDEX USA - Chicago**  
 300 SOUTH WACKER DRIVE, SUITE 1500  
 CHICAGO, IL  
 US 60606  
 Contact: DEVIN LINEHAN  
 DLinehan@nordex-online.com  
 T: (312)386-4124  
 F: (312)386-7102

Certificate L2367  
 To discuss this sample report, contact Customer Service at 1-800-237-1369.  
 \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.  
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)