


FUEL REPORT

[PMOAS3121499] 14377840100 (S/N 2116602)

Component **Diesel Fuel**

No.2 DIESEL FUEL (LOW-SULPHUR) (350 GAL)





Recommendation

All laboratory tests indicate that this sample meets specifications for No.2 ultra-low-sulfur diesel fuel.

Corrosion

All metal levels are normal indicating no corrosion in the system.

Contaminants

The water content is negligible. There is no bacteria or fungus (yeast and/or mold) indicated in the sample. There is no indication of any contamination in the fuel.

Fuel Condition


Sulfur value derived by ASTM D5453 method for ULSD validation. Sulfur level is acceptable for ULSD specification.


GAL)		Sep2017	Dec2019	Nov2020 Oct2023	Feb 2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		DC0033999	DC0031445	WCDF02490
Sample Date		Client Info		21 Feb 2024	11 Oct 2023	09 Nov 2020
Machine Age	hrs	Client Info		564	0	372
Sample Status				NORMAL	NORMAL	NORMAL
PHYSICAL PROP	ERTIES	method	limit/base	current	history1	history2
ASTM Color	scalar	*ASTM D1500		L4.5	L4.5	L5.5
Visc @ 40°C	cSt	ASTM D445	3.0	2.46	2.46	2.3
SULFUR CONTE	NT	method	limit/base	current	history1	history2
Sulfur	ppm	ASTM D5185m	250	3	197	9
Sulfur (UVF)	ppm	ASTM D5453		10	11	10
IGNITION QUALIT	ГΥ	method	limit/base	current	history1	history2
API Gravity		ASTM D7777	37.7	36.9	36.7	38.1
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	<1.0	<1	0	<1
Sodium	ppm	ASTM D5185m	<0.1	<1	<1	<1
Potassium	ppm	ASTM D5185m	< 0.1	<1	0	0
Water	%	ASTM D6304	< 0.05	0.003	0.003	0.003
ppm Water	ppm	ASTM D6304	< 500	38	28.9	25.4
% Gasoline	%	*In-House	< 0.50	0.0	0.0	0.0
% Biodiesel	%	*In-House	<20.0	0.0	0.0	0.0
HEAVY METALS		method	limit/base	current	history1	history2
Aluminum	ppm	ASTM D5185m	<0.1	0	0	<1
Nickel	ppm	ASTM D5185m	< 0.1	0	0	0
Lead	ppm	ASTM D5185m	< 0.1	0	0	0
Vanadium	ppm	ASTM D5185m	< 0.1	0	0	0
Iron	ppm	ASTM D5185m	< 0.1	0	0	0
Calcium	ppm	ASTM D5185m	< 0.1	2	0	<1
Magnesium	ppm	ASTM D5185m	< 0.1	0	0	0
Phosphorus	ppm	ASTM D5185m	< 0.1	<1	0	2
Zinc	ppm	ASTM D5185m	<0.1	0	0	4
SAMPLE IMAGES	3	method	limit/base	current	history1	history2
Color						


Bottom



FUEL REPORT









Laboratory Sample No. Unique Number : 10896291

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : DC0033999 Lab Number : 06098061

Received **Tested**

: 22 Feb 2024 : 27 Feb 2024 Diagnosed

: 27 Feb 2024 - Doug Bogart **Test Package**: DF-5 (Additional Tests: API, Cetane, Fuel, Screen)

KELLY GENERATOR & EQUIPMENT INC 1955 DALE LN OWINGS, MD US 20736

Contact: LESLIE SNURR LSNURR@KGE.COM T: (410)257-5225

Contact/Location: LESLIE SNURR - KELOWI

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: (410)257-5227