




OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



Machine Id

6629

Component

Diesel Engine

Fluid

DIESEL ENGINE OIL SAE 15W40 (16 GAL)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor. Please specify the component make and model with your next sample.

Wear

Metal levels are typical for a new component breaking in.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		WC0871024	WC06027471	WC0694234
Sample Date	Client Info		07 Dec 2023	06 Dec 2023	28 Sep 2022
Machine Age	mls	Client Info	16165	0	138711
Oil Age	mls	Client Info	450	0	450
Oil Changed	Client Info		Changed	N/A	N/A
Sample Status			NORMAL	NORMAL	NORMAL

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>5	<1.0	<1.0	<1.0
Water	WC Method	>0.2	NEG	NEG	NEG
Glycol	WC Method		NEG	NEG	NEG

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >100	2	4	10
Chromium	ppm	ASTM D5185m >20	0	0	<1
Nickel	ppm	ASTM D5185m >4	0	0	0
Titanium	ppm	ASTM D5185m	0	0	0
Silver	ppm	ASTM D5185m >3	0	0	0
Aluminum	ppm	ASTM D5185m >20	<1	1	<1
Lead	ppm	ASTM D5185m >40	0	0	2
Copper	ppm	ASTM D5185m >330	0	<1	<1
Tin	ppm	ASTM D5185m >15	<1	0	<1
Antimony	ppm	ASTM D5185m	---	---	---
Vanadium	ppm	ASTM D5185m	0	0	0
Cadmium	ppm	ASTM D5185m	0	0	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 250	14	1	6
Barium	ppm	ASTM D5185m 10	0	0	<1
Molybdenum	ppm	ASTM D5185m 100	54	56	61
Manganese	ppm	ASTM D5185m	0	<1	<1
Magnesium	ppm	ASTM D5185m 450	766	940	915
Calcium	ppm	ASTM D5185m 3000	1058	1092	1206
Phosphorus	ppm	ASTM D5185m 1150	924	1039	990
Zinc	ppm	ASTM D5185m 1350	1039	1242	1249
Sulfur	ppm	ASTM D5185m 4250	2859	3064	3029

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >25	3	4	4
Sodium	ppm	ASTM D5185m >158	1	3	0
Potassium	ppm	ASTM D5185m >20	0	<1	2

INFRA-RED



	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.6	0.4	0.4
Nitration	Abs/cm	*ASTM D7624 >20	12.9	8.4	10.1
Sulfation	Abs/.1mm	*ASTM D7415 >30	23.1	19.6	22.6

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	22.7	15.2	18.4
Base Number (BN)	mg KOH/g	ASTM D2896 8.5	4.1	7.7	9.0











OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2	
Visc @ 100°C	cSt	ASTM D445	14.4	13.8	13.7	14.0

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : WC0871024 **Received** : 23 Feb 2024
Lab Number : 06098179 **Tested** : 25 Feb 2024
Unique Number : 10896409 **Diagnosed** : 25 Feb 2024 - Wes Davis
Test Package : MOB 1 (Additional Tests: TBN)

INTERSTATE WASTE-CHESTER
 89 BLACK MEADOW RD
 CHESTER, NY
 US 10918
 Contact: ROB CLARKE
 rclarke@interstatewaste.com
 T:
 F: (845)572-3301

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)