




OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL



Area
FOUR MILE RIDGE [200005315]
 Machine Id
83309 SITE 5
 Component
Wind Turbine Gearbox
 Fluid
CASTROL OPTIGEAR SYNTHETIC X 320 (--- LTR)

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the component. The amount and size of particulates present in the system is acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		NX012335	NX012348	NX05620732
Sample Date	Client Info		16 Oct 2023	22 Mar 2023	01 Jun 2022
Machine Age	hrs	Client Info	69591	63375	0
Oil Age	hrs	Client Info	69591	63375	0
Oil Changed	Client Info		Not Changed	Not Changed	N/A
Sample Status			NORMAL	NORMAL	NORMAL

WEAR METALS

	method	limit/base	current	history1	history2
PQ	ASTM D8184	>80	15	12	21
Iron	ppm	ASTM D5185m	>150	4	2
Chromium	ppm	ASTM D5185m	>5	<1	0
Nickel	ppm	ASTM D5185m	>10	<1	0
Titanium	ppm	ASTM D5185m	>10	<1	0
Silver	ppm	ASTM D5185m		<1	0
Aluminum	ppm	ASTM D5185m	>10	4	<1
Lead	ppm	ASTM D5185m	>20	<1	0
Copper	ppm	ASTM D5185m	>50	2	<1
Tin	ppm	ASTM D5185m	>10	0	0
Vanadium	ppm	ASTM D5185m		<1	0
Cadmium	ppm	ASTM D5185m		<1	0

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1	0
Barium	ppm	ASTM D5185m		8	0
Molybdenum	ppm	ASTM D5185m	1150	757	749
Manganese	ppm	ASTM D5185m		<1	<1
Magnesium	ppm	ASTM D5185m		4	9
Calcium	ppm	ASTM D5185m	2000	1456	1465
Phosphorus	ppm	ASTM D5185m	400	308	339
Zinc	ppm	ASTM D5185m	0	7	0
Sulfur	ppm	ASTM D5185m	1850	1981	1693

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	13	10
Sodium	ppm	ASTM D5185m	>20	1	4
Potassium	ppm	ASTM D5185m	>20	1	0
Water	%	ASTM D6304	>0.05	0.019	0.009
ppm Water	ppm	ASTM D6304	>500	193	93.1

FLUID CLEANLINESS






	method	limit/base	current	history1	history2
Particles >4µm	ASTM D7647		269	679	1358
Particles >6µm	ASTM D7647	>2500	31	50	277
Particles >14µm	ASTM D7647	>320	4	4	23
Particles >21µm	ASTM D7647	>80	2	2	7
Particles >38µm	ASTM D7647	>20	1	0	1
Particles >71µm	ASTM D7647	>4	0	0	0
Oil Cleanliness	ISO 4406 (c)	>--/18/15	15/12/9	17/13/9	18/15/12

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.6	0.62	0.89




OIL ANALYSIS REPORT








VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	320	320	315

SAMPLE IMAGES	method	limit/base	current	history1	history2
---------------	--------	------------	---------	----------	----------



GRAPHS



Certificate L2367

Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : NX012335
Lab Number : 06098388
Unique Number : 10896618
Test Package : IND 2 (Additional Tests: KF, PQ, PrtCount)

NORDEX USA - Chicago
 300 SOUTH WACKER DRIVE, SUITE 1500
 CHICAGO, IL
 US 60606

Received : 23 Feb 2024
Tested : 26 Feb 2024
Diagnosed : 26 Feb 2024 - Don Baldrige
Contact: DEVIN LINEHAN
 DLinehan@nordex-online.com
 T: (312)386-4124
 F: (312)386-7102

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)