


OIL ANALYSIS REPORT



 $^{\text{Machine Id}}_{7606900}$ (S/N 1139)

Component

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Aug	2022	Mar2023 Feb20	24	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCP36784	KCPA000239	KCP49941
Sample Date		Client Info		09 Feb 2024	20 Mar 2023	19 Aug 2022
Machine Age	hrs	Client Info		14936	9824	5390
Oil Age	hrs	Client Info		9370	0	5390
Oil Changed		Client Info		Not Changd	N/A	Changed
Sample Status				ATTENTION	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	<1	0	0
Titanium	ppm	ASTM D5185m	>3	<1	0	0
Silver	ppm	ASTM D5185m	>2	<1	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	1	4
Lead	ppm	ASTM D5185m	>10	<1	0	0
Copper	ppm	ASTM D5185m	>50	8	6	10
Tin	ppm	ASTM D5185m	>10	<1	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		<1	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	5	0	0
Molybdenum	ppm	ASTM D5185m		<1	0	0
Manganese	ppm	ASTM D5185m		<1	<1	0
Magnesium	ppm	ASTM D5185m	90	<1	2	2
Calcium	ppm	ASTM D5185m	2	0	0	0
Phosphorus	ppm	ASTM D5185m		0	1	2
Zinc	ppm	ASTM D5185m		2	0	0
Sulfur	ppm	ASTM D5185m		13286	15779	16691
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	1	1	1
Sodium	ppm	ASTM D5185m		0	0	0
Potassium	ppm	ASTM D5185m	>20	<1	0	<1
Water	%	ASTM D6304	>0.05	0.018	0.006	0.006
ppm Water	ppm	ASTM D6304	>500	187	66.5	64.2
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		4351	1385	1518
Particles >6µm		ASTM D7647	>1300	1362	482	418
Particles >14μm		ASTM D7647	>80	112	42	41
Particles >21µm		ASTM D7647	>20	9 31	8	8
Particles >38μm		ASTM D7647	>4	1	0	1
Particles >71μm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/18/14	18/16/13	18/16/13
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma K∩U/a	VCTM D804E	0.4	0.44	0.44	0.41

Acid Number (AN)

mg KOH/g ASTM D8045 0.4

0.44

0.44

0.41



OIL ANALYSIS REPORT

