


## **OIL ANALYSIS REPORT**

# AIRLUBE 228 [1405458]

**ATLAS COPCO AIF026-329 - AK STEEL DIRECT AIR** 

Component

Compressor



Sample Rating Trend



#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Oct2009	Apr2010 Oct2010	Feb 2012 Oct 2012 Ju	2012 Oct2012 Jul2023			
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2		
Sample Number		Client Info		UCH06098516	UCH05910125	UCH05720671		
Sample Date		Client Info		05 Feb 2024	03 Jul 2023	15 Nov 2022		
Machine Age	hrs	Client Info		176321	171680	166374		
Oil Age	hrs	Client Info		6641	2156	6060		
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd		
Sample Status				NORMAL	NORMAL	NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2		
Water		WC Method	>0.1	NEG	NEG	NEG		
WEAR METALS		method	limit/base	current	history1	history2		
Iron	ppm	ASTM D5185m	>50	0	<1	<1		
Chromium	ppm	ASTM D5185m	>5	0	0	0		
Nickel	ppm	ASTM D5185m		<1	0	0		
Titanium	ppm	ASTM D5185m		0	0	0		
Silver	ppm	ASTM D5185m		0	0	0		
Aluminum	ppm	ASTM D5185m	>15	16	16	2		
Lead	ppm	ASTM D5185m	>65	0	0	0		
Copper	ppm	ASTM D5185m	>65	<1	<1	<1		
Tin	ppm	ASTM D5185m	>10	0	0	0		
Antimony	ppm	ASTM D5185m						
Vanadium	ppm	ASTM D5185m		0	0	0		
Cadmium	ppm	ASTM D5185m		0	0	0		
ADDITIVES		method	limit/base	current	history1	history2		
Boron	ppm	ASTM D5185m	1.5	0	0	0		
Barium	ppm	ASTM D5185m	0	0	0	0		
Molybdenum	ppm	ASTM D5185m	0	0	0	0		
Manganese	ppm	ASTM D5185m	0.3	<1	0	0		
Magnesium	ppm	ASTM D5185m	0	<1	0	<1		
Calcium	ppm	ASTM D5185m	0	<1	0	0		
Phosphorus	ppm	ASTM D5185m	406	131	109	86		
Zinc	ppm	ASTM D5185m	0	0	0	0		
Sulfur	ppm	ASTM D5185m	1283	<1	<1	533		
CONTAMINANTS	;	method	limit/base	current	history1	history2		
Silicon	ppm	ASTM D5185m	>35	0	0	<1		
Sodium	ppm	ASTM D5185m		2	0	<1		
Potassium	ppm	ASTM D5185m	>20	<1	<1	0		
FLUID DEGRADA	NOITA	method	limit/base	current	history1	history2		
A atal Nicosala au (ANI)		4 OTM DOC 45	0.400	0.04	0.00	0.50		

0.94

Acid Number (AN)


mg KOH/g ASTM D8045 0.463


0.39

0.52




## **OIL ANALYSIS REPORT**








VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
<b>Emulsified Water</b>	scalar	*Visual	>0.1	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	47.9	52.6	50.5	47.0
CANADI E INAAOEO			1111.//		In the Landson and	le le termino


Color


















Certificate L2367

Laboratory Sample No.

Test Package : IND 2

: UCH06098516 Lab Number : 06098516 Unique Number : 10896746

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Received : 23 Feb 2024 **Tested** 

: 26 Feb 2024 Diagnosed : 26 Feb 2024 - Don Baldridge **AIR TECHNOLOGIES INC (MID)** 

400 WRIGHT AVE MIDDLETOWN, OH US 45044

Contact: Josh Oaks

F: (513)539-6040

josh.oaks@aircompressors.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: UCAIRMID [WUSCAR] 06098516 (Generated: 02/26/2024 15:05:45) Rev: 1

Contact/Location: Josh Oaks - UCAIRMID

T: