

OIL ANALYSIS REPORT

Sample Rating Trend



KAESER SFC 18S 6045711 (S/N 1002)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| | | Jun2019 | Nov2019 Sep2020 | Jun2021 Jan2023 Aug2023 | Jan2024 | |
|-----------------|--------|--------------|-----------------|-------------------------|-----------------|-----------------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | KCPA011063 | KCPA004431 | KCP47489 |
| Sample Date | | Client Info | | 12 Jan 2024 | 03 Aug 2023 | 23 Jan 2023 |
| Machine Age | hrs | Client Info | | 47443 | 43393 | 39362 |
| Oil Age | hrs | Client Info | | 0 | 0 | 3757 |
| Oil Changed | | Client Info | | N/A | N/A | Not Changd |
| Sample Status | | | | ABNORMAL | ABNORMAL | ABNORMAL |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >50 | 0 | <1 | <1 |
| Chromium | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Nickel | ppm | ASTM D5185m | >3 | 0 | <1 | 0 |
| Titanium | ppm | ASTM D5185m | >3 | 0 | 0 | 0 |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >10 | 0 | <1 | 0 |
| Lead | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Copper | ppm | ASTM D5185m | >50 | 9 | 20 | 12 |
| Tin | ppm | ASTM D5185m | >10 | 0 | 0 | 0 |
| Antimony | ppm | ASTM D5185m | | | | |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | 90 | 0 | 0 | 2 |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Magnesium | ppm | ASTM D5185m | 100 | 0 | 1 | 2 |
| Calcium | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Phosphorus | ppm | ASTM D5185m | 0 | 0 | 0 | 2 |
| Zinc | ppm | ASTM D5185m | 0 | 4 | 15 | 27 |
| Sulfur | ppm | ASTM D5185m | 23500 | 16363 | 22611 | 18239 |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >25 | <1 | 2 | 1 |
| Sodium | ppm | ASTM D5185m | | 3 | 0 | 0 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | <1 | <1 |
| Water | % | ASTM D6304 | >0.05 | 0.004 | 0.009 | 0.008 |
| ppm Water | ppm | ASTM D6304 | >500 | 50 | 92.2 | 83.0 |
| FLUID CLEANLIN | IESS | method | limit/base | current | history1 | history2 |
| Particles >4μm | | ASTM D7647 | | 17702 | 23974 | 36111 |
| Particles >6µm | | ASTM D7647 | | <u>4841</u> | <u>11492</u> | ▲ 8932 |
| Particles >14μm | | ASTM D7647 | >80 | <u> </u> | <u>1386</u> | <u>^</u> 233 |
| Particles >21µm | | ASTM D7647 | >20 | <u>^</u> 26 | ▲ 301 | 36 |
| Particles >38µm | | ASTM D7647 | >4 | 0 | 3 | 3 |
| Particles >71µm | | ASTM D7647 | >3 | 0 | 0 | 0 |
| Oil Cleanliness | | ISO 4406 (c) | >/17/13 | <u>21/19/15</u> | <u>22/21/18</u> | <u>22/20/15</u> |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |

0.47



OIL ANALYSIS REPORT

