


# **OIL ANALYSIS REPORT**

Sample Rating Trend



**NORMAL** 

# Machine Id KAESER BSD 50 8023216 (S/N 1194)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Ma	·2022	Jan 2023 Feb 203	24	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA002571	KCP55762	KCP41042
Sample Date		Client Info		07 Feb 2024	31 Jan 2023	11 Mar 2022
Machine Age	hrs	Client Info		13205	7040	2600
Oil Age	hrs	Client Info		0	4440	2600
Oil Changed		Client Info		N/A	Changed	Changed
Sample Status				NORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	0	<1	<1
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	10	15	4
Tin	ppm	ASTM D5185m	>10	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	<1
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	100	0	0	36
Calcium	ppm	ASTM D5185m	0	0	0	1
Phosphorus	ppm	ASTM D5185m	0	0	14	6
Zinc	ppm	ASTM D5185m	0	0	0	7
Sulfur	ppm	ASTM D5185m	23500	14223	17097	16009
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	5	<1
Sodium	ppm	ASTM D5185m		1	0	6
Potassium	ppm	ASTM D5185m	>20	0	0	2
Water	%	ASTM D6304	>0.05	0.003	<b>△</b> 0.249	<b>△</b> 0.795
ppm Water	ppm	ASTM D6304	>500	31	<u>^</u> 2490	<b>△</b> 7950
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		2788	1044	
Particles >6µm		ASTM D7647	>1300	538	569	
Particles >14µm		ASTM D7647	>80	23	<b>4</b> 97	
Particles >21μm		ASTM D7647	>20	5	<b>3</b> 3	
Particles >38µm		ASTM D7647	>4	1	<b>5</b>	
Particles >71μm		ASTM D7647	>3	0	1	
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/16/12	<b>1</b> 7/16/14	
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.47	0.38	0.39



## **OIL ANALYSIS REPORT**

