


**OIL ANALYSIS REPORT** 

KAESER 4708730

Component

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)





## Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

## Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

## **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

			Sep 2022	Jan 2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA011029	KCP50122	
Sample Date		Client Info		22 Jan 2024	16 Sep 2022	
Machine Age	hrs	Client Info		6600	6446	
Oil Age	hrs	Client Info		0	0	
Oil Changed		Client Info		N/A	Changed	
Sample Status				NORMAL	ABNORMAL	
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	
Chromium	ppm	ASTM D5185m	>10	0	0	
Nickel	ppm	ASTM D5185m	>3	0	<1	
Titanium	ppm	ASTM D5185m	>3	0	0	
Silver	ppm	ASTM D5185m	>2	0	0	
Aluminum	ppm	ASTM D5185m	>10	0	0	
Lead	ppm	ASTM D5185m	>10	0	0	
Copper	ppm	ASTM D5185m	>50	3	11	
Tin	ppm	ASTM D5185m	>10	0	0	
Vanadium	ppm	ASTM D5185m		0	0	
Cadmium	ppm	ASTM D5185m		0	0	
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	
Barium	ppm	ASTM D5185m	90	38	0	
Molybdenum	ppm	ASTM D5185m		0	0	
Manganese	ppm	ASTM D5185m		<1	<1	
Magnesium	ppm	ASTM D5185m	90	61	18	
Calcium	ppm	ASTM D5185m	2	0	0	
Phosphorus	ppm	ASTM D5185m		0	13	
Zinc	ppm	ASTM D5185m		10	52	
Sulfur	ppm	ASTM D5185m		16291	20823	
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	
Sodium	ppm	ASTM D5185m		15	9	
Potassium	ppm	ASTM D5185m	>20	2	5	
Water	%	ASTM D6304	>0.05	0.015	0.023	
ppm Water	ppm	ASTM D6304	>500	158	239.9	
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		3425	75180	
Particles >6µm		ASTM D7647	>1300	905	<u>\$\text{25524}\$</u>	
Particles >14µm		ASTM D7647	>80	52	<u> </u>	
Particles >21µm		ASTM D7647	>20	11	<u>175</u>	
Particles >38µm		ASTM D7647	>4	0	<u>^</u> 6	
Particles >71µm		ASTM D7647	>3	0	0	
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/17/13	<u>\$\text{23}/22/18}</u>	
FLUID DEGRADA	TION _	method	limit/base	current	history1	history2
Asid Number (AN)		ACTM DODAE	0.4	0.26	0.25	

Acid Number (AN)

mg KOH/g ASTM D8045 0.4

0.35

0.36



# **OIL ANALYSIS REPORT**

