


OIL ANALYSIS REPORT

COMPRESSOR STATIONS/RED HILLS EAST AREA Machine Id CABALLO (S/N 5629X2455)

Component

Compressor

TULCO LUBSOIL LPG WS 150 (--- GAL)





DIAGNOSIS

Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Dec2022 Apr2023 Feb2024				
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60002083	TO60000848	TO70000201
Sample Date		Client Info		25 Feb 2024	12 Apr 2023	20 Dec 2022
Machine Age	hrs	Client Info		0	30705	28172
Oil Age	hrs	Client Info		0	30705	22288
Oil Changed		Client Info		N/A	Filtered	Filtered
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3	<u></u> 59	23
Chromium	ppm	ASTM D5185m	>10	<1	<1	0
Nickel	ppm	ASTM D5185m		<1	<1	0
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	0	<1
Lead	ppm	ASTM D5185m	>25	0	0	<1
Copper	ppm	ASTM D5185m	>50	<1	<1	0
Tin	ppm	ASTM D5185m	>15	0	1	2
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	2	0
Barium	ppm	ASTM D5185m	0	8	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	0	<1	4	1
Calcium	ppm	ASTM D5185m	0	2	5	1
Phosphorus	ppm	ASTM D5185m	0	92	162	62
Zinc	ppm	ASTM D5185m	0	27	10	5
Sulfur	ppm	ASTM D5185m	0	2848	1754	1231
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	<1
Sodium	ppm	ASTM D5185m		22	9	5
Potassium	ppm	ASTM D5185m	>20	4	2	<1
Water	%	ASTM D6304	>2.26	0.613	0.845	0.475
ppm Water	ppm	ASTM D6304	>22600	6136	8450	4750
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<u> </u>	2542	△ 61284
Particles >6µm		ASTM D7647	>1300	<u> </u>	692	<u></u> 16416
Particles >14μm		ASTM D7647	>320	191	46	<u> </u>
Particles >21μm		ASTM D7647	>80	37	12	▲ 310
Particles >38μm		ASTM D7647	>20	6	0	<u>^</u> 21
Particles >71μm		ASTM D7647	>4	4	0	3
Oil Cleanliness		ISO 4406 (c)	>20/17/15	<u>21/19/15</u>	19/17/13	<u>△</u> 23/21/17
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.73	0.76	0.43



OIL ANALYSIS REPORT

