


OIL ANALYSIS REPORT

COMPRESSOR STATIONS/RED HILLS EAST AREA **BRONCO (S/N LE10363)**

Component

Compressor

TULCO LUBSOIL LPG WS 150 (--- GAL)





DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Dec202	2 Apr2023	Aug ² 023 Fi	b2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60002082	TO60001220	TO60000846
Sample Date		Client Info		25 Feb 2024	15 Aug 2023	10 Apr 2023
Machine Age	hrs	Client Info		0	11991	12630
Oil Age	hrs	Client Info		0	11991	4588
Oil Changed		Client Info		N/A	Oil Added	Filtered
Sample Status				ABNORMAL	ATTENTION	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	2	<1	1
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m		0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	3	0
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>50	0	0	0
Tin	ppm		>15	0	1	<1
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES	•••	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	2	<1
Barium	ppm		0	8	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m	0	0	0	0
Magnesium	ppm	ASTM D5185m	0	<1	2	<1
Calcium	ppm	ASTM D5185m		2	0	1
Phosphorus		ASTM D5185m	0	28	2	5
Zinc	ppm	ASTM D5185m	0	0	0	1
Sulfur	ppm	ASTM D5185m	0	73	136	9
	ppm					
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	<1
Sodium	ppm	ASTM D5185m		2	0	<1
Potassium	ppm	ASTM D5185m	>20	2	1	<1
Water	%	ASTM D6304		0.651	0.664	0.614
ppm Water	ppm	ASTM D6304	>22600	6514	6642.4	6140
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<u>A</u> 83983	5626	5192
Particles >6μm		ASTM D7647	>1300	<u> </u>	1964	1103
Particles >14μm		ASTM D7647	>320	252	100	65
Particles >21μm		ASTM D7647	>80	41	12	17
Particles >38μm		ASTM D7647	>20	0	0	3
Particles >71μm		ASTM D7647	>4	0	0	2
Oil Cleanliness		ISO 4406 (c)	>20/17/15	<u>4</u> 24/20/15	20/18/14	20/17/13
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Asid Number (ANI)	ma K∩U/a	ACTM DODAE		0.44	0.00	0.17

Acid Number (AN)

mg KOH/g ASTM D8045

0.29

0.41

0.17



OIL ANALYSIS REPORT

