

# **OIL ANALYSIS REPORT**



# COMPRESSOR STATIONS/RED HILLS WEST AREA VALOR (S/N 5629X2172)

Component

Compressor

**TULCO LUBSOIL LPG WS 150 (--- GAL)** 

**DIAGNOSIS** 

### Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

All component wear rates are normal.

### Contamination

There is a high amount of particulates present in the oil.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SIS REPORT	Sample Rating Trend						
LLS WEST AREA							
	Apr2022	May2022	Nov2022	Apr2023	Aug2023	Feb 2024	
SAMPLE INFORMATION	method	limit/b	oase	cu	rrent	ŀ	

Sample Number		Client Info		TO60002026	TO60001214	TO60000806
Sample Date		Client Info		06 Feb 2024	10 Aug 2023	13 Apr 2023
Machine Age	hrs	Client Info		37750	33716	30920
Oil Age	hrs	Client Info		0	3114	27454
Oil Changed		Client Info		N/A	N/A	Not Changd
Sample Status				ABNORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	2	6	37
Chromium	ppm	ASTM D5185m		- <1	0	<1
Nickel	ppm	ASTM D5185m		0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	<1
Aluminum	ppm	ASTM D5185m	>25	2	<1	0
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m		0	<1	0
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium		ASTM D5185m	>10	0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	<1
	ppm			-		
ADDITIVES		method	limit/base		history1	history2
Boron	ppm	ASTM D5185m	0	0	0	1
Barium	ppm	ASTM D5185m	0	8	0	1
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	0	<1	2	3
Calcium	ppm	ASTM D5185m	0	2	0	2
Phosphorus	ppm	ASTM D5185m	0	127	19	52
Zinc	ppm	ASTM D5185m	0	0	0	18
Sulfur	ppm	ASTM D5185m	0	1316	377	1067
CONTAMINANTS	<b>;</b>	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	<1
Sodium	ppm	ASTM D5185m		10	10	28
Potassium	ppm	ASTM D5185m	>20	2	2	3
Water	%	ASTM D6304	>2.26	0.959	2.232	0.936
ppm Water	ppm	ASTM D6304	>22600	9598	22327.2	9360
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<b>▲ 34763</b>	3201	▲ 31195
Particles >6µm		ASTM D7647	>1300	<u> </u>	817	2193
Particles >14µm		ASTM D7647	>320	<u> </u>	70	108
Particles >21µm		ASTM D7647	>80	<u> </u>	20	27
Particles >38µm		ASTM D7647	>20	2	2	2
Particles >71µm		ASTM D7647	>4	1	1	1
Oil Cleanliness		ISO 4406 (c)	>20/17/15	<u>22/21/17</u>	19/17/13	<u>22/18/14</u>
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.75	0.40	0.50



## **OIL ANALYSIS REPORT**

