


OIL ANALYSIS REPORT

RED HILLS WEST GOLDEN BEAR (S/N LE11193)

Compressor

TULCO LUBSOIL LPG WS 150 (--- GAL)





Recommendation

No corrective action is recommended at this time. Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is a moderate amount of silt (particulates < 14 microns in size) present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jul2022	Nov2022	Apr2023 Aug2023	Feb 2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60002028	TO60001212	TO60000808
Sample Date		Client Info		06 Feb 2024	10 Aug 2023	13 Apr 2023
Machine Age	hrs	Client Info		15630	10205	8463
Oil Age	hrs	Client Info		0	1800	4198
Oil Changed		Client Info		N/A	Not Changd	N/A
Sample Status				ATTENTION	ATTENTION	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	1	2
Chromium	ppm	ASTM D5185m	>10	<1	0	1
Nickel	ppm	ASTM D5185m		0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	1
Aluminum	ppm	ASTM D5185m	>25	2	<1	0
Lead	ppm	ASTM D5185m	>25	0	0	<1
Copper	ppm	ASTM D5185m	>50	<1	<1	<1
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	1
Cadmium	ppm	ASTM D5185m		0	0	1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	<1
Barium	ppm	ASTM D5185m	0	8	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	<1
Manganese	ppm	ASTM D5185m		0	<1	<1
Magnesium	ppm	ASTM D5185m	0	2	1	<1
Calcium	ppm	ASTM D5185m	0	1	0	2
Phosphorus	ppm	ASTM D5185m	0	25	7	3
Zinc	ppm	ASTM D5185m	0	0	0	0
Sulfur	ppm	ASTM D5185m	0	269	295	45
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	2
Sodium	ppm	ASTM D5185m		1	3	27
Potassium	ppm	ASTM D5185m	>20	2	2	6
Water	%	ASTM D6304	>2.26	0.178	0.626	0.365
ppm Water	ppm	ASTM D6304	>22600	1788	6265.3	3650
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	4993	5884	5493
Particles >6µm		ASTM D7647	>1300	<u> </u>	1413	480
Particles >14μm		ASTM D7647	>320	158	89	25
Particles >21µm		ASTM D7647	>80	34	14	6
Particles >38μm		ASTM D7647	>20	0	1	1
Particles >71μm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/17/15	19/18/14	0 20/18/14	20/16/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.24	0.18	0.16



OIL ANALYSIS REPORT

