


OIL ANALYSIS REPORT

COMPRESSOR STATIONS/RED HILLS EAST AREA JAFAR (S/N 5329X4370)

Component

Compressor

TULCO LUBSOIL LPG WS 150 (--- GAL)





DIAGNOSIS

Recommendation

We recommend you service the filters on this component. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Dec202	2 Apr2023	Aug2023 Fe	b2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60002075	TO60001221	TO70000253
Sample Date		Client Info		16 Feb 2024	15 Aug 2023	11 Apr 2023
Machine Age	hrs	Client Info		0	56221	53234
Oil Age	hrs	Client Info		0	56221	53234
Oil Changed		Client Info		N/A	Oil Added	Filtered
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	<1
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m		0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	3	0
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>50	0	0	<1
Tin	ppm	ASTM D5185m	>15	0	1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	2
Barium	ppm	ASTM D5185m	0	8	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	0	<1	1	<1
Calcium	ppm	ASTM D5185m	0	<1	0	1
Phosphorus	ppm	ASTM D5185m	0	34	68	91
Zinc	ppm	ASTM D5185m	0	0	0	2
Sulfur	ppm	ASTM D5185m	0	201	321	540
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	<1
Sodium	ppm	ASTM D5185m		4	8	8
Potassium	ppm	ASTM D5185m	>20	3	2	<1
Water	%	ASTM D6304	>2.26	0.152	0.342	1.06
ppm Water	ppm	ASTM D6304	>22600	1526	3423.0	10600
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	23729	<u>^</u> 29939	<u>^</u> 20117
Particles >6µm		ASTM D7647	>1300	A 7817	<u>^</u> 7410	<u></u> 5840
Particles >14µm		ASTM D7647	>320	<u></u> 541	301	192
Particles >21µm		ASTM D7647	>80	<u> 102</u>	56	22
Particles >38µm		ASTM D7647	>20	1	2	1
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/17/15	22/20/16	<u>22/20/15</u>	△ 22/20/15
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.22	0.28	0.21



OIL ANALYSIS REPORT

