


## **OIL ANALYSIS REPORT**

# COMPRESSOR STATIONS/ROSS DRAW AREA **DOVE (S/N LE11333)**

Component

Compressor

**TULCO LUBSOIL LPG WS 150 (--- GAL)** 





### **DIAGNOSIS**

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

#### Contamination

There is a high amount of particulates present in the oil.

#### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		May2023 Feb20		Aug2023 Feb20	24	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		TO60002091	TO60001245	TO60000850
Sample Date		Client Info		07 Feb 2024	09 Aug 2023	05 May 2023
Machine Age	hrs	Client Info		11707	2817	4320
Oil Age	hrs	Client Info		4320	4320	4320
Oil Changed		Client Info		Filtered	N/A	N/A
Sample Status				ABNORMAL	NORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	1
Chromium	ppm	ASTM D5185m	>10	<1	0	<1
Nickel	ppm	ASTM D5185m		0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	<1
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	2	<1	0
Lead	ppm	ASTM D5185m	>25	0	0	0
Copper	ppm	ASTM D5185m	>50	0	<1	0
Tin	ppm	ASTM D5185m	>15	0	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	0	8	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	0	<1	2	<1
Calcium	ppm	ASTM D5185m	0	<1	0	2
Phosphorus	ppm	ASTM D5185m	0	25	3	4
Zinc	ppm	ASTM D5185m	0	0	0	0
Sulfur	ppm	ASTM D5185m	0	87	34	71
CONTAMINANTS	<b>,</b>	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	14
Sodium	ppm	ASTM D5185m		4	2	6
Potassium	ppm	ASTM D5185m	>20	1	2	<1
Water	%	ASTM D6304	>2.26	0.181	0.266	0.298
ppm Water	ppm	ASTM D6304	>22600	1810	2662.1	2980
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	<b>27030</b>	933	<u>▲</u> 139284
Particles >6µm		ASTM D7647	>1300	<b>4</b> 9298	248	<u>▲</u> 51371
Particles >14µm		ASTM D7647	>320	<b>938</b>	18	<b>▲</b> 1517
Particles >21μm		ASTM D7647	>80	<b>4</b> 236	7	158
Particles >38µm		ASTM D7647	>20	4	0	3
Particles >71µm		ASTM D7647	>4	0	0	0
Oil Cleanliness		ISO 4406 (c)	>20/17/15	<u>22/20/17</u>	17/15/11	<u>4</u> 24/23/18
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.21	0.089	0.105



## **OIL ANALYSIS REPORT**

