

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area LSS-9300-5 Machine Id QUINCY 95581 - PACTIV Component

Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06101061		
Sample Date		Client Info		05 Feb 2024		
Machine Age	hrs	Client Info		49971		
Oil Age	hrs	Client Info		7671		
Oil Changed		Client Info		N/A		
Sample Status				NORMAL		
CONTAMINATIO	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	2		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		8		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		<1		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		220		
Zinc	ppm	ASTM D5185m		0		
Sulfur	ppm	ASTM D5185m		514		
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2		
Sodium	ppm	ASTM D5185m		0		
Potassium	ppm	ASTM D5185m	>20	1		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.68		



0.70 0.60 (B/H0) 0.50 Ê 0.40 e 0.30 Acid Nur 0.10 0.00 Feb5/24

> 52 Abnormal 50 48 (J-046 (J-046 44 42 40 Abnorma

> > 38 Feb5/24 -

Acid Number

Viscosity @ 40°C

OIL ANALYSIS REPORT

		VISUAL		method	limit/base	current	history1	history2
		White Metal	scalar	*Visual	NONE	NONE		
		Yellow Metal	scalar	*Visual	NONE	NONE		
		Precipitate	scalar	*Visual	NONE	NONE		
		Silt	scalar		NONE	NONE		
		Debris	scalar	*Visual	NONE	NONE		
		Sand/Dirt	scalar	*Visual	NONE	NONE		
	Feb 5/24	Appearance	scalar	*Visual	NORML	NORML		
	ш.	Odor		*Visual	NORML	NORML		
		Emulsified Water	scalar	*Visual	>0.1	NEG		
		Free Water	scalar	*Visual		NEG		
		FLUID PROPERT	IES	method	limit/base	current	history1	history2
		Visc @ 40°C	cSt	ASTM D445		47.0		
		SAMPLE IMAGES			limit/bees		history1 -	biotom/2
		SAMPLE IMAGES	5	method	limit/base	current	history1	history2
	Feb5/24 +	Color					no image	no image
		Bottom					no image	no image
		Ferrous Alloys						
		ud 4 2 0 4 2 2 0 4 2 2 0 4 2 2 0 4 2 2 0 4 2 2 0 4 2 2 2 0 4 2 2 3 0 10 10 10 10 10 10 10 10 10 10 10 10 1			Feb5/24			
		Non-ferrous Metal	s					
		8- 6- 4-						
		2 +			Feb5/24			
		Viscosity @ 40°C			0.80	Acid Number		
		50 - Abnormal			NO 0 60			1
					E 0.40			
	100000	€ 45 -						
	100000	45 - 45 - 45 - 40 - Abnormal			plumbe			
		40 Abnormal			Mundar Mu			
		40 Abnormal			(0.80 (0)HOX 0.60 Bull yau at the second sec			5/24
Sam Lab	oratory : ple No. : Number :	40 Abnormal	1 Madiso Recei Teste Diagn	ved : 26 d : 27	Feb5/24	LEWIS :		ERVICE CO INC FOCKPORT PL IARLOTTE, NC US 28273

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Contact/Location: JOE KERLEY - UCLEWCHA