




OIL ANALYSIS REPORT

Sample Rating Trend



WEAR



Area
SCHTRUCK
 Machine Id
6500 [SCHTRUCK]

Component
Diesel Engine
 Fluid
PETRO CANADA DURON SHP 15W40 (10 GAL)

DIAGNOSIS

Recommendation

Oil and filter change at the time of sampling has been noted. No corrective action is recommended at this time. Resample at the next service interval to monitor.

Wear

The copper level has decreased, but is still abnormal. All other component wear rates are normal.

Contamination

Elevated aluminum (Al) and/or lead (Pb) and potassium (K) levels in your metals analysis are likely a result of solder flux release into the lubricant and is common on new equipment/components. No other contaminants were detected in the oil.

Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

SAMPLE INFORMATION

	method	limit/base	current	history1	history2
Sample Number	Client Info		SBP0007060	SBP0005899	---
Sample Date	Client Info		12 Mar 2024	01 Nov 2023	---
Machine Age	hrs	Client Info	76500	39541	---
Oil Age	hrs	Client Info	36959	39541	---
Oil Changed	Client Info		Changed	Changed	---
Sample Status			ABNORMAL	ABNORMAL	---

CONTAMINATION

	method	limit/base	current	history1	history2
Fuel	WC Method	>3.0	<1.0	0.4	---
Water	WC Method	>0.2	NEG	NEG	---
Glycol	WC Method		NEG	NEG	---

WEAR METALS

	method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m >200	62	128	---
Chromium	ppm	ASTM D5185m >20	4	7	---
Nickel	ppm	ASTM D5185m >2	1	2	---
Titanium	ppm	ASTM D5185m >2	0	0	---
Silver	ppm	ASTM D5185m >2	0	<1	---
Aluminum	ppm	ASTM D5185m >30	20	65	---
Lead	ppm	ASTM D5185m >30	<1	0	---
Copper	ppm	ASTM D5185m >30	▲ 51	▲ 469	---
Tin	ppm	ASTM D5185m >15	3	9	---
Vanadium	ppm	ASTM D5185m	0	0	---
Cadmium	ppm	ASTM D5185m	0	0	---

ADDITIVES

	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m 0	3	37	---
Barium	ppm	ASTM D5185m 0	0	0	---
Molybdenum	ppm	ASTM D5185m 60	63	60	---
Manganese	ppm	ASTM D5185m 0	2	6	---
Magnesium	ppm	ASTM D5185m 1010	966	710	---
Calcium	ppm	ASTM D5185m 1070	1308	2208	---
Phosphorus	ppm	ASTM D5185m 1150	1017	935	---
Zinc	ppm	ASTM D5185m 1270	1264	1205	---
Sulfur	ppm	ASTM D5185m 2060	2375	2656	---

CONTAMINANTS

	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m >30	8	13	---
Sodium	ppm	ASTM D5185m	3	10	---
Potassium	ppm	ASTM D5185m >20	47	165	---

INFRA-RED






	method	limit/base	current	history1	history2
Soot %	%	*ASTM D7844 >3	0.8	0.7	---
Nitration	Abs/cm	*ASTM D7624 >20	11.3	13.0	---
Sulfation	Abs/.1mm	*ASTM D7415 >30	22.8	24.4	---

FLUID DEGRADATION

	method	limit/base	current	history1	history2
Oxidation	Abs/.1mm	*ASTM D7414 >25	24.4	30.9	---
Base Number (BN)	mg KOH/g	ASTM D2896 9.8	5.7	5.8	---







OIL ANALYSIS REPORT



VISUAL	method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	---
Yellow Metal	scalar	*Visual	NONE	NONE	---
Precipitate	scalar	*Visual	NONE	NONE	---
Silt	scalar	*Visual	NONE	NONE	---
Debris	scalar	*Visual	NONE	NONE	---
Sand/Dirt	scalar	*Visual	NONE	NONE	---
Appearance	scalar	*Visual	NORML	NORML	---
Odor	scalar	*Visual	NORML	NORML	---
Emulsified Water	scalar	*Visual	>0.2	NEG	---
Free Water	scalar	*Visual		NEG	---

FLUID PROPERTIES	method	limit/base	current	history1	history2
Visc @ 100°C	cSt	ASTM D445	15.4	13.1	10.5

GRAPHS



Laboratory : WearCheck USA - 501 Madison Ave., Cary, NC 27513
Sample No. : SBP0007060 **Received** : 18 Mar 2024
Lab Number : 06121446 **Tested** : 19 Mar 2024
Unique Number : 10930279 **Diagnosed** : 20 Mar 2024 - Don Baldrige
Test Package : FLEET

SCHMIDT TRANSPORTATION - 605449
 108 E Bay Road
 Plattsmouth, NE
 US 68048
 Contact: NICK DOTY
 doty@liquidtrucking.com
 T: (402)949-9398
 F:

To discuss this sample report, contact Customer Service at 1-800-237-1369.
 * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.
 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)