


OIL ANALYSIS REPORT

Sample Rating Trend



NORMAL



VSS-01 (S/N 3409)

Component

Refrigeration Compressor

VILTER 717 COMPRESSOR OIL ISO 68 (--- GAL)

Dirtartoolo

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

| GAL) | | Aug2018 Ma | z2019 Oct2019 Jul202 | 20 Dec2021 Sep2022 May20 | 23 Mar2024 | |
|------------------|----------|--------------|----------------------|--------------------------|-------------|-------------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | USP0006098 | USP248146 | USP248145 |
| Sample Date | | Client Info | | 18 Mar 2024 | 17 Sep 2023 | 31 May 2023 |
| Machine Age | hrs | Client Info | | 73055 | 71133 | 67256 |
| Oil Age | hrs | Client Info | | 0 | 0 | 0 |
| Oil Changed | | Client Info | | N/A | N/A | Not Changd |
| Sample Status | | | | NORMAL | NORMAL | ATTENTION |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| Iron | ppm | ASTM D5185m | >8 | 0 | 0 | 0 |
| Chromium | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Nickel | ppm | ASTM D5185m | | 0 | <1 | 0 |
| Titanium | ppm | ASTM D5185m | | 0 | 0 | <1 |
| Silver | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Aluminum | ppm | ASTM D5185m | >3 | 0 | 0 | <1 |
| Lead | ppm | ASTM D5185m | >2 | 0 | 0 | 0 |
| Copper | ppm | ASTM D5185m | >8 | 0 | 0 | 0 |
| Tin | ppm | ASTM D5185m | >4 | 0 | 0 | 0 |
| Vanadium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Cadmium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Barium | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Molybdenum | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Manganese | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Magnesium | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Calcium | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Phosphorus | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Zinc | ppm | ASTM D5185m | 0 | 0 | 0 | 0 |
| Sulfur | ppm | ASTM D5185m | | 0 | 0 | 0 |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >15 | 0 | 0 | <1 |
| Sodium | ppm | ASTM D5185m | | 0 | 0 | 0 |
| Potassium | ppm | ASTM D5185m | >20 | 0 | <1 | 0 |
| Water | % | ASTM D6304 | >0.01 | 0.001 | 0.001 | 0.001 |
| ppm Water | ppm | ASTM D6304 | >100 | 0 | 0.00 | 0.00 |
| FLUID CLEANLIN | ESS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | >10000 | 7143 | 2052 | 12056 |
| Particles >6μm | | ASTM D7647 | >2500 | 1017 | 439 | 2609 |
| Particles >14μm | | ASTM D7647 | >320 | 32 | 20 | 50 |
| Particles >21μm | | ASTM D7647 | | 8 | 8 | 7 |
| Particles >38μm | | ASTM D7647 | >20 | 0 | 1 | 1 |
| Particles >71μm | | ASTM D7647 | | 0 | 0 | 0 |
| Oil Cleanliness | | ISO 4406 (c) | >20/18/15 | 20/17/12 | 18/16/11 | 21/19/13 |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |
| Acid Number (AN) | mg KOH/g | ASTM D974 | 0.2 | 0.014 | 0.015 | 0.015 |



OIL ANALYSIS REPORT





Certificate L2367

Laboratory Sample No. Lab Number

: USP0006098

: 06122439 Unique Number: 10936590 Test Package : IND 2

Received **Tested**

Diagnosed

: 19 Mar 2024 : 20 Mar 2024

: 20 Mar 2024 - Doug Bogart

GREAT LAKES CHEESE 2200 ENTERPRISE AVE LA CROSSE, WI

US 54602

Contact: Service Manager

To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T:

F: