


OIL ANALYSIS REPORT

[604160956 SDR] **CONDENSON PUMP (S/N 20037579)**

Component

Gearbox

GEAR OIL ISO 220 (--- GAL)





Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		WC0854405	WC0562252	WC0605571
Sample Date		Client Info		03 Mar 2024	08 Sep 2023	05 Mar 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		Changed	Changed	Changed
Sample Status				NORMAL	NORMAL	NORMAL
CONTAMINATION	V	method	limit/base	current	history1	history2
Water		WC Method	>0.2	NEG	NEG	NEG
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>200	6	18	<1
Chromium	ppm	ASTM D5185m	>15	0	2	0
Nickel	ppm	ASTM D5185m	>15	0	<1	<1
Titanium	ppm	ASTM D5185m		0	0	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>25	0	6	<1
Lead	ppm	ASTM D5185m	>100	0	0	0
Copper	ppm	ASTM D5185m	>200	0	0	0
Tin	ppm	ASTM D5185m	>25	0	0	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	50	0	0	0
Barium	ppm	ASTM D5185m	15	0	0	0
Molybdenum	ppm	ASTM D5185m	15	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	50	0	2	<1
Calcium	ppm	ASTM D5185m	50	0	3	2
Phosphorus	ppm	ASTM D5185m	350	199	255	180
Zinc	ppm	ASTM D5185m	100	0	<1	0
Sulfur	ppm	ASTM D5185m	12500	2121	1948	1798
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>50	4	7	2
Sodium	ppm	ASTM D5185m		0	0	<1
Potassium	ppm	ASTM D5185m	>20	0	0	<1
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.85	0.75	0.64	0.72




OIL ANALYSIS REPORT




Mar24/	Mar14/	Mar7,	Mar13/	Mar5/	Mar3/
Viscos	ity @ 40	0°C			
Base 200 Abnorma				_	
(0.04) 150			\vee		
50					
Mar24/19	Mar14/20	Mar7/2	Mar13/22	Mar5/23	Mar3/24


VISUAL		method				history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.2	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	TIES	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	220	216	216	217
SAMPLE IMAGES		method	limit/base	current	history1	history2


Color


















Certificate L2367

Laboratory Sample No. Unique Number : 10936714

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 Lab Number : 06122563

: WC0854405

Received **Tested** Diagnosed

: 19 Mar 2024 : 20 Mar 2024

: 21 Mar 2024 - Jonathan Hester

MARS CHOCOLATE 2019 NORTH OAK PARK CHICAGO, IL

US 60707 Contact: TONY FIORE

tony.fiore@effem.com T: (773)745-2279

Test Package : IND 2 To discuss this sample report, contact Customer Service at 1-800-237-1369.

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation. Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: MARSCHI [WUSCAR] 06122563 (Generated: 03/21/2024 19:27:35) Rev: 1

Contact/Location: TONY FIORE - MARSCHI