

OIL ANALYSIS REPORT

Sample Rating Trend **NORMAL**

[] NOT GIVEN WC0845868

Diesel Engine

{not provided} (--- GAL)

Recommendation

Resample at the next service interval to monitor.

All component wear rates are normal.

Contamination

There is no indication of any contamination in the


Fluid Condition

The BN result indicates that there is suitable alkalinity remaining in the oil. The condition of the oil is suitable for further service.

				Mar2024			
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2	
	VIZTION	Client Info	mmoasc				
Sample Number		Client Info		WC0845868 18 Mar 2024			
Sample Date	lawa						
Machine Age	hrs	Client Info		0			
Oil Changed	IIIS	Client Info		N/A			
Oil Changed		Cilent inio		NORMAL			
Sample Status				NONWAL			
CONTAMINATIO	N	method	limit/base	current	history1	history2	
Fuel		WC Method	>5	<1.0			
Glycol		WC Method		NEG			
WEAR METALS		method	limit/base	current	history1	history2	
Iron	ppm	ASTM D5185m	>100	10			
Chromium	ppm	ASTM D5185m	>20	0			
Nickel	ppm	ASTM D5185m	>4	0			
Titanium	ppm	ASTM D5185m		0			
Silver	ppm	ASTM D5185m	>3	0			
Aluminum	ppm	ASTM D5185m	>20	0			
Lead	ppm	ASTM D5185m	>40	9			
Copper	ppm	ASTM D5185m	>330	34			
Tin	ppm	ASTM D5185m	>15	0			
Vanadium	ppm	ASTM D5185m		0			
Cadmium	ppm	ASTM D5185m		0			
ADDITIVES		method	limit/base	current	history1	history2	
Boron	ppm	ASTM D5185m		21			
Barium	ppm	ASTM D5185m		0			
Molybdenum	ppm	ASTM D5185m		44			
Manganese	ppm	ASTM D5185m		0			
Magnesium	ppm	ASTM D5185m		1246			
Calcium	ppm	ASTM D5185m		1573			
Phosphorus	ppm	ASTM D5185m		945			
Zinc	ppm	ASTM D5185m		1259			
Sulfur	ppm	ASTM D5185m		3015			
CONTAMINANTS	5	method	limit/base	current	history1	history2	
Silicon	ppm	ASTM D5185m	>25	1			
Sodium	ppm	ASTM D5185m		<1			
Potassium	ppm	ASTM D5185m	>20	<1			
Water	%	ASTM D6304	>0.2	NEG			
INFRA-RED		method	limit/base	current	history1	history2	
Soot %	%	*ASTM D7844	>3	0.1			
Nitration	Abs/cm	*ASTM D7624		12.7			
Sulfation	Abs/.1mm	*ASTM D7415		25.4			
FLUID DEGRADATION method limit/base current history1 history2							
Oxidation	Abs/.1mm	*ASTM D7414	>25	27.5			
ONIUGUOU	LINO/ IIIIII	70 HW D/414	/20	21.5			
Base Number (BN)	mg KOH/g	ASTM D2896		8.34			




OIL ANALYSIS REPORT





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
Emulsified Water	scalar	*Visual	>0.2	NEG		
Free Water	scalar	*Visual		NEG		
FLUID PROPERT	IES	method	limit/base	current	history1	history2


FLUID PHOPER	TILO	method		riistory i	HISTORYZ
Visc @ 100°C	cSt	ASTM D445	15.6		

GRAPHS











Laboratory Sample No. Lab Number : 06122615 Unique Number : 10936766

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : WC0845868

Received

Tested Diagnosed Test Package : IND 2 (Additional Tests: KF)

: 21 Mar 2024 : 21 Mar 2024 - Jonathan Hester

: 19 Mar 2024

MARATHON PETROLEUM CO.

101 12TH ST CATLETTSBURG, KY US 41169

Contact: CORY GUMBERT cagumbert@marathonpetroleum.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. * - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

T: (606)585-3950 Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012) F: x:

Report Id: MARCAT [WUSCAR] 06122615 (Generated: 03/21/2024 19:39:41) Rev: 1

Contact/Location: CORY GUMBERT - MARCAT