

## **OIL ANALYSIS REPORT**

### INGERSOLL RAND IR-2 NEW (S/N V3087U17040) Component

**Air Compressor** Fluic

USPI AIR 46 (--- GAL)

#### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil. The amount and size of particulates present in the system are acceptable.

#### Fluid Condition

An increase in the AN level is noted. Confirmed. The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.







SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		USPM36874	USPM31902	USPM29413
Sample Date		Client Info		15 Mar 2024	06 Dec 2023	22 Aug 2023
Machine Age	hrs	Client Info		0	0	0
Oil Age	hrs	Client Info		0	0	0
Oil Changed		Client Info		N/A	N/A	N/A
Sample Status				NORMAL	NORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3	<1	0
Chromium	ppm	ASTM D5185m	>4	<1	0	0
Nickel	ppm	ASTM D5185m	>4	0	0	0
Titanium	ppm	ASTM D5185m		0	<1	0
Silver	ppm	ASTM D5185m		0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	<1	0
Lead	ppm	ASTM D5185m	>20	0	0	0
Copper	ppm		>40	8	4	6
Tin	ppm	ASTM D5185m	>5	<1	<1	<1
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	0	0	0	0
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	0	0	0	0
Calcium	ppm	ASTM D5185m	0	<1	0	0
Phosphorus	ppm	ASTM D5185m	1	0	0	9
Zinc	ppm	ASTM D5185m	0	198	32	24
Sulfur	ppm	ASTM D5185m	0	18	0	52
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	1	<1
Sodium	ppm	ASTM D5185m		<1	0	<1
Potassium	ppm	ASTM D5185m	>20	0	2	0
Water	%	ASTM D6304	>0.2	0.078	0.043	0.104
ppm Water	ppm	ASTM D6304	>2000	788	437	1047.3
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	2710	715	1788
Particles >6µm		ASTM D7647	>2500	673	326	587
Particles >14µm		ASTM D7647	>320	53	56	66
Particles >21µm		ASTM D7647	>80	11	11	19
Particles >38µm		ASTM D7647	>20	1	0	2
Particles >71µm		ASTM D7647	>4	0	0	1
Oil Cleanliness		ISO 4406 (c)	>20/18/15	19/17/13	17/16/13	18/16/13
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.05	0.638	0.38	0.34


Contact/Location: DANNY HOUSTON - TYSWALAR




# **OIL ANALYSIS REPORT**










### r of particles (1 ml) 8k 6 4k 2 0 C/ C C 40 Laboratory Sample No. Lab Number Certificate L2367



Bottom



To discuss this sample report, contact Customer Service at 1-800-237-1369.

\* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

T: (479)637-2121

F: (479)637-5602