

OIL ANALYSIS REPORT

Sample Rating Trend



history2

KAESER AS 25T 3478474 (S/

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

/N 1492)					
	Sep2015	Aug2017 Aug20	21 Oct2022 Sep	2023 Mar2024	
SAMPLE INFORMATION	method	limit/base	e curre	nt	history1
ample Number	Client Info		KCPA015	359 KCF	A004506
ample Date	Client Info		11 Mar 20	24 01 S	Sep 2023

Sample Number		Client Info		KCPA015359	KCPA004506	KCP46776D
Sample Date		Client Info		11 Mar 2024	01 Sep 2023	25 Oct 2022
Machine Age	hrs	Client Info		26503	25552	23942
Oil Age	hrs	Client Info		0	0	5000
Oil Changed		Client Info		Not Changd	N/A	Changed
Sample Status				ABNORMAL	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3	<1	0
Chromium	ppm	ASTM D5185m	>10	<1	0	<1
Nickel	ppm	ASTM D5185m	>3	0	0	<1
Titanium	ppm	ASTM D5185m	>3	0	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	<1	0	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	3	2	3
Tin	ppm	ASTM D5185m	>10	0	0	<1
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	<1
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		3	0	<1
Manganese	ppm	ASTM D5185m		<1	<1	1
Magnesium	ppm	ASTM D5185m	90	34	36	41
Calcium	ppm	ASTM D5185m	2	<1	0	0
Phosphorus	ppm	ASTM D5185m		0	1	<1
Zinc	ppm	ASTM D5185m		15	9	10
Sulfur	ppm	ASTM D5185m		22892	23122	22403
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	1
Sodium	ppm	ASTM D5185m		12	3	11
Potassium	ppm	ASTM D5185m	>20	0	0	1
Water	%	ASTM D6304	>0.05	0.013	△ 0.309	0.020
ppm Water	ppm	ASTM D6304	>500	134	▲ 3090	204.4
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		8434	3784	11147
Particles >6µm		ASTM D7647	>1300	<u> </u>	<u>^</u> 2062	<u></u> 5006
Particles >14µm		ASTM D7647	>80	207	△ 351	<u></u> 872
Particles >21µm		ASTM D7647	>20	△ 62	<u></u> 118	<u></u> 186
Particles >38µm		ASTM D7647	>4	4	<u> </u>	<u>^</u> 7
Particles >71µm		ASTM D7647	>3	0	2	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>^</u> 20/18/15	<u>19/18/16</u>	<u>^</u> 21/20/17
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

0.32



OIL ANALYSIS REPORT

