

# **OIL ANALYSIS REPORT**

## KAESER AIRCENTER SX5 4659902 (S/N 1198) Component

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

#### Recommendation

Resample at the next service interval to monitor.

#### Wear


All component wear rates are normal.

#### Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.



SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA015392	KCP50526	KCP39568
Sample Date		Client Info		08 Mar 2024	16 Aug 2022	23 Nov 2021
Machine Age	hrs	Client Info		53642	49356	46950
Oil Age	hrs	Client Info		205	2405	0
Oil Changed		Client Info		Not Changd	Not Changd	Changed
Sample Status				NORMAL	SEVERE	ATTENTION
· · ·	_					
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	3	0	0
Chromium	ppm	ASTM D5185m	>10	<1	0	0
Nickel	ppm	ASTM D5185m	>3	0	<1	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	<1	0
Aluminum	ppm	ASTM D5185m	>10	<1	2	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	<1	12	14
Tin	ppm	ASTM D5185m	>10	0	1	0
Antimony	ppm	ASTM D5185m				
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
	ppiii		11 11 11			
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	<1	<1
Barium	ppm	ASTM D5185m	90	88	0	0
Molybdenum	ppm	ASTM D5185m		3	0	0
Manganese	ppm	ASTM D5185m		<1	0	0
Magnesium	ppm	ASTM D5185m	90	89	13	10
Calcium	ppm	ASTM D5185m	2	4	0	0
Phosphorus	ppm	ASTM D5185m		2	<1	10
Zinc	ppm	ASTM D5185m		0	31	43
Sulfur	ppm	ASTM D5185m		22065	16761	15639
CONTAMINANTS	6	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	<1	<1
Sodium	ppm	ASTM D5185m		2	0	8
Potassium	ppm	ASTM D5185m	>20	0	0	<1
Water	%	ASTM D6304	>0.05	0.019	▲ 0.105	0.004
ppm Water	ppm	ASTM D6304	>500	194	<b>1</b> 050	41.0
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		1833		8186
Particles >6µm		ASTM D7647	>1300	335		91901
Particles >14µm		ASTM D7647	>80	21		134
Particles >21µm		ASTM D7647		6		39
Particles >38µm		ASTM D7647	>4	0		3
Particles >71µm		ASTM D7647		0		0
Oil Cleanliness		ISO 4406 (c)	>/17/13	0 18/16/12		18/14
		( )				
FLUID DEGRADA	ATION	method	limit/base		history1	history2
Acid Number (AN)	ma K∩⊔/a	ACTM DOME	0.4	0.20	0.10	0.16

mg KOH/g ASTM D8045 0.4 Acid Number (AN)


Report Id: HOBOKL [WUSCAR] 06123189 (Generated: 03/21/2024 20:28:22) Rev: 1


0.38 0.19 0.16 Contact/Location: JEFF LEWIS - HOBOKL


Page 1 of 2




# **OIL ANALYSIS REPORT**










VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	NONE	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	VLITE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	0.2%	NEG
Free Water	scalar	*Visual		NEG	▲ >10%	NEG
FLUID PROPERTIES		method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	46	45.6	44.0	43.2
SAMPLE IMAGES		method	limit/base	current	history1	history2
Color						
_				1000		

Bottom



Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)