

OIL ANALYSIS REPORT

Sample Rating Trend





A

201405290038

Component

Air Compressor

SULLAIR SULLUBE (3 GAL)

DIAGNOSIS

Recommendation

We advise that you follow the water drain-off procedure for this component. The filter change at the time of sampling has been noted. We recommend an early resample to monitor this condition.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil. There is a high concentration of water present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		İ				
				Jan2024		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		SFA0000064		
Sample Date		Client Info		24 Jan 2024		
Machine Age	hrs	Client Info		7846		
Oil Age	hrs	Client Info		7846		
Oil Changed		Client Info		Not Changd		
Sample Status				ABNORMAL		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>4	0		
Nickel	ppm	ASTM D5185m	>4	0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>10	0		
Lead	ppm	ASTM D5185m	>20	0		
Copper	ppm	ASTM D5185m		1		
Tin	ppm	ASTM D5185m	>5	1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES	1-1-	method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		<1		
Barium	ppm	ASTM D5185m	7/15	328		
Molybdenum		ASTM D5185m	0.0	0		
	ppm	ASTM D5185m	0.0	<1		
Manganese Magnesium	ppm	ASTM D5185m	0.0	<1		
Calcium	ppm		1	4		
	ppm	ASTM D5185m		-		
Phosphorus	ppm	ASTM D5185m	3	3		
Zinc	ppm	ASTM D5185m	0.1	0		
Sulfur	ppm	ASTM D5185m	240	286		
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	2		
Sodium	ppm	ASTM D5185m		37		
Potassium	ppm	ASTM D5185m	>20	4		
Water	%	ASTM D6304	>0.6	△ 0.860		
opm Water	ppm	ASTM D6304	>6000	<u>▲</u> 8600		
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647	>10000	15489		
Particles >6µm		ASTM D7647		4869		
Particles >14μm		ASTM D7647	>320	630		
Particles >21µm		ASTM D7647	>80	<u>207</u>		
Particles >38μm		ASTM D7647	>20	10		
Particles >71μm		ASTM D7647	>4	1		
Oil Cleanliness		ISO 4406 (c)	>20/18/15	2 1/19/16		
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	.06	0.188		



OIL ANALYSIS REPORT

