


#### **OIL ANALYSIS REPORT**

## SULLUBE 32 [3309780] Machine Id SULLAIR 202003060006 - TWB CO

Component

Compressor



#### DIAGNOSIS

#### Recommendation

Resample at the next service interval to monitor.

#### Moor

All component wear rates are normal.

#### Contamination

There is no indication of any contamination in the oil


#### Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				Marzuza		
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCS06123813		
Sample Date		Client Info		15 Mar 2024		
Machine Age	hrs	Client Info		21294		
Oil Age	hrs	Client Info		7470		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	2		
Chromium	ppm	ASTM D5185m	>10	0		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	<1		
Tin	ppm	ASTM D5185m	>15	0		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m	745	852		
Molybdenum	ppm	ASTM D5185m		0		
Manganese	ppm	ASTM D5185m		0		
Magnesium	ppm	ASTM D5185m		2		
Calcium	ppm	ASTM D5185m	1	4		
Phosphorus	ppm	ASTM D5185m	3	0		
Zinc	ppm	ASTM D5185m		16		
Sulfur	ppm	ASTM D5185m		478		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0		
Sodium	ppm	ASTM D5185m		50		
Potassium	ppm	ASTM D5185m	>20	5		
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.33		

### **Sullivan**


#### **OIL ANALYSIS REPORT**





VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE		
Yellow Metal	scalar	*Visual	NONE	NONE		
Precipitate	scalar	*Visual	NONE	NONE		
Silt	scalar	*Visual	NONE	NONE		
Debris	scalar	*Visual	NONE	NONE		
Sand/Dirt	scalar	*Visual	NONE	NONE		
Appearance	scalar	*Visual	NORML	NORML		
Odor	scalar	*Visual	NORML	NORML		
<b>Emulsified Water</b>	scalar	*Visual	>0.1	NEG		
Free Water	scalar	*Visual		NEG		
	IFC		Para St /In an ana		la balla second	la la tarre O
FLUID PROPERT	IES .	method	limit/base	current	history1	history2
Visc @ 40°C	cSt	ASTM D445	32.0	41.2		
SAMPLE IMAGES	;	method	limit/base	current	history1	history2
<u> </u>						

Color no image no image **Bottom** no image no image **GRAPHS** 

# Ferrous Alloys Non-ferrous Metals











Certificate L2367

Laboratory Sample No.

Lab Number : 06123813 Unique Number : 10937964 Test Package : IND 2

: WearCheck USA - 501 Madison Ave., Cary, NC 27513 : UCS06123813

Received **Tested** Diagnosed

: 20 Mar 2024 : 21 Mar 2024

: 22 Mar 2024 - Don Baldridge

**PROCESS & POWER - NASHVILLE** 138 BAIN DRIVE LA VERGNE, TN US 37086

Contact: LORI GATES Igates@pnpmail.com

To discuss this sample report, contact Customer Service at 1-800-237-1369. \* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

Report Id: PRONAS [WUSCAR] 06123813 (Generated: 03/22/2024 19:25:58) Rev: 1

Contact/Location: LORI GATES - PRONAS

T:

F: