


OIL ANALYSIS REPORT

Sample Rating Trend



Machino Id

KAESER SFC 55 4846724 (S/N 1053)

Component

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor. We were unable to perform a particle count due to a high concentration of particles present in this sample.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of visible silt present in the sample.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jul2014	Jul2017 Jul2018	Mar2021 Nov2021 Jan2023	Mar2024	
SAMPLE INFORI	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA015715	KCP55114	KCP43358
Sample Date		Client Info		13 Mar 2024	12 Jan 2023	12 Nov 2021
Machine Age	hrs	Client Info		35739	32529	28681
Oil Age	hrs	Client Info		0	1891	3526
Oil Changed		Client Info		Not Changd	Not Changd	Not Changd
Sample Status				ABNORMAL	NORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	<1
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	<1
Aluminum	ppm	ASTM D5185m	>10	0	0	0
Lead	ppm	ASTM D5185m	>10	0	0	<1
Copper	ppm	ASTM D5185m	>50	12	7	16
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m				0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	<1
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	2
Barium	ppm	ASTM D5185m	90	0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m	90	0	14	0
Calcium	ppm	ASTM D5185m	2	0	<1	0
Phosphorus	ppm	ASTM D5185m		0	9	2
Zinc	ppm	ASTM D5185m		0	16	0
Sulfur	ppm	ASTM D5185m		17810	18866	13332
CONTAMINANTS	3	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	<1	<1
Sodium	ppm	ASTM D5185m		6	15	18
Potassium	ppm	ASTM D5185m	>20	0	4	2
Water	%	ASTM D6304	>0.05	0.010	0.013	0.022
ppm Water	ppm	ASTM D6304	>500	101	139.6	222.8
FLUID CLEANLIN	NESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647			587	6498
Particles >6µm		ASTM D7647	>1300		210	2209
Particles >14µm		ASTM D7647	>80		8	116
Particles >21μm		ASTM D7647	>20		2	33
Particles >38µm		ASTM D7647	>4		0	1
Particles >71µm		ASTM D7647	>3		0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13		16/15/10	18/14
FLUID DEGRADA	ATION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045 0.4


Contact/Location: M HURLEY - UNICHAKC


0.31


0.306



OIL ANALYSIS REPORT







VISUAL		method	limit/base	current	history1	history2
White Metal	scalar	*Visual	NONE	NONE	NONE	LIGHT
Yellow Metal	scalar	*Visual	NONE	NONE	NONE	NONE
Precipitate	scalar	*Visual	NONE	NONE	NONE	NONE
Silt	scalar	*Visual	NONE	▲ MODER	NONE	NONE
Debris	scalar	*Visual	NONE	NONE	NONE	NONE
Sand/Dirt	scalar	*Visual	NONE	NONE	NONE	NONE
Appearance	scalar	*Visual	NORML	NORML	NORML	NORML
Odor	scalar	*Visual	NORML	NORML	NORML	NORML
Emulsified Water	scalar	*Visual	>0.05	NEG	NEG	NEG
Free Water	scalar	*Visual		NEG	NEG	NEG
FLUID PROPERT	IES	method	limit/base	current	history1	history2

SAMPLE IMAGES	method	limit/base	current	history1	history2

43.9

ASTM D445 46

Color

Visc @ 40°C




cSt





43.9


42.3

GRAPHS













Laboratory Sample No. Lab Number : 06124298 Unique Number : 10938449

: WearCheck USA - 501 Madison Ave., Cary, NC 27513

: KCPA015715

Received **Tested** Diagnosed

: 20 Mar 2024 : 23 Mar 2024

: 23 Mar 2024 - Don Baldridge

UNITED ENERTECH 3005 S HICKORY ST CHATTANOOGA, TN US 37407

Test Package: IND 2 (Additional Tests: KF, PrtCount) To discuss this sample report, contact Customer Service at 1-800-237-1369.

Contact: M HURLEY mhurley@unitedenertech.com T:

* - Denotes test methods that are outside of the ISO 17025 scope of accreditation.

Statements of conformity to specifications are based on the simple acceptance decision rule (JCGM 106:2012)

F: