

OIL ANALYSIS REPORT

Sample Rating Trend

NORMAL

Area ASL 46 [1612] Machine Id CHICAGO PNEUMATIC ITJ001109 - ERS

Compressor

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is no indication of any contamination in the oil.


Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

				Mar2024		
SAMPLE INFORM	IATION	method	limit/base	current	history1	history2
Sample Number		Client Info		UCH06124964		
Sample Date		Client Info		12 Mar 2024		
Machine Age	hrs	Client Info		17098		
Oil Age	hrs	Client Info		1275		
Oil Changed		Client Info		Changed		
Sample Status				NORMAL		
CONTAMINATION	N	method	limit/base	current	history1	history2
Water		WC Method	>0.1	NEG		
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0		
Chromium	ppm	ASTM D5185m	>10	<1		
Nickel	ppm	ASTM D5185m		0		
Titanium	ppm	ASTM D5185m		0		
Silver	ppm	ASTM D5185m		0		
Aluminum	ppm	ASTM D5185m	>25	0		
Lead	ppm	ASTM D5185m	>25	0		
Copper	ppm	ASTM D5185m	>50	1		
Tin	ppm	ASTM D5185m	>15	<1		
Vanadium	ppm	ASTM D5185m		0		
Cadmium	ppm	ASTM D5185m		0		
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0		
Barium	ppm	ASTM D5185m		2		
Molybdenum	ppm	ASTM D5185m		<1		
Manganese	ppm	ASTM D5185m		<1		
Magnesium	ppm	ASTM D5185m		0		
Calcium	ppm	ASTM D5185m		0		
Phosphorus	ppm	ASTM D5185m		219		
Zinc	ppm	ASTM D5185m		38		
Sulfur	ppm	ASTM D5185m		1318		
CONTAMINANTS	;	method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1		
Sodium	ppm	ASTM D5185m		<1		
Potassium	ppm	ASTM D5185m	>20	0		
FLUID DEGRADA		method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045		0.131		



OIL ANALYSIS REPORT



	VISUAL		method	limit/base	current	history1	history2
	White Metal	scalar	*Visual	NONE	NONE		
	Yellow Metal	scalar	*Visual	NONE	NONE		
	Precipitate	scalar	*Visual	NONE	NONE		
	Silt	scalar	*Visual	NONE	NONE		
	Debris	scalar	*Visual	NONE	LIGHT		
	Sand/Dirt	scalar	*Visual	NONE	NONE		
Mar1 2/24	Appearance	scalar	*Visual	NORML	NORML		
M	Odor	scalar	*Visual	NORML	NORML		
	Emulsified Water	scalar	*Visual	>0.1	NEG		
1	Free Water	scalar	*Visual		NEG		
	FLUID PROPER	TIES	method	limit/base	current	history1	history2
	Visc @ 40°C	cSt	ASTM D445		44.5		
	SAMPLE IMAGE	S	method	limit/base	current	history1	history2
Mar12/24	Color					no image	no image
	Bottom					no image	no image
	GRAPHS						
	Ferrous Alloys						
	10 8						
	- 6 - nickel						
	2						
				2			
	Mar12/24			Mar12/24			
	—	1		Ň			
	Non-ferrous Meta	IS					
	8 copper						
	8 - copper lead						
	8 - copper lead						
	8 - copper lead						
	B Copper			24			
	B Copper			Aar12/24			
	ead tin tin tin tin			Mart 2/24			
	B Copper				Acid Number		
	Viscosity @ 40°C				Acid Number		
	Viscosity @ 40°C				Acid Number		
	viscosity @ 40°C				Acid Number		
	viscosity @ 40°C			0.15. 0.10 grupped (mg K0H/g) 0.05.	Acid Number		
	Viscosity @ 40°C			0.15- 0.100 KOH(d) 0.050 Vorumper 0.050 Vorumper			28
	viscosity @ 40°C			0.15. 0.10 grupped (mg K0H/g) 0.05.	Acid Number		10,272.2
Laboratory Sample No. Lab Number Unique Number Test Package	WearCheck USA - 50 : UCH06124964 : 10939115	Recei Teste	ived : 21 ed : 25	Mar12/24 0.0.0 Acid Number (mg KOH(g) 0.000	47271mm AIR SPE(DE	MENT COMPAN 314 EAST P S EER PARK, T) US 77536 : AARON RIOS

ē

Contact/Location: AARON RIOS - UCAIRDEE