

OIL ANALYSIS REPORT

MAGENTA NTX [200007685] Machine Id 26WEA91137

Component

Hydraulic System

SHELL TELLUS S4 VX 32 (--- LTR)

Sample Rating Trend ADDITIVES Mad2024

DIAGNOSIS

Recommendation

Resample at the next service interval to monitor.

Moor

All component wear rates are normal.

Contamination

The amount and size of particulates present in the system are acceptable. There is no indication of any contamination in the oil.

Fluid Condition

Additive levels indicate the addition of a different brand, or type of oil. The AN level is acceptable for this fluid.

| | | 1 | | Mar2024 | | |
|-----------------|--------|--------------|------------|-------------|----------|----------|
| SAMPLE INFORM | MATION | method | limit/base | current | history1 | history2 |
| Sample Number | | Client Info | | NX012243 | | |
| Sample Date | | Client Info | | 05 Mar 2024 | | |
| Machine Age | hrs | Client Info | | 0 | | |
| Oil Age | hrs | Client Info | | 0 | | |
| Oil Changed | | Client Info | | N/A | | |
| Sample Status | | | | ATTENTION | | |
| WEAR METALS | | method | limit/base | current | history1 | history2 |
| PQ | | ASTM D8184 | | 15 | | |
| Iron | ppm | ASTM D5185m | >20 | 0 | | |
| Chromium | ppm | ASTM D5185m | >20 | 0 | | |
| Nickel | ppm | ASTM D5185m | >20 | 0 | | |
| Titanium | ppm | ASTM D5185m | | 0 | | |
| Silver | ppm | ASTM D5185m | | 0 | | |
| Aluminum | ppm | ASTM D5185m | >20 | 0 | | |
| Lead | ppm | ASTM D5185m | >20 | 0 | | |
| Copper | ppm | ASTM D5185m | >20 | 2 | | |
| Tin | ppm | ASTM D5185m | >20 | 0 | | |
| Vanadium | ppm | ASTM D5185m | | 0 | | |
| Cadmium | ppm | ASTM D5185m | | 0 | | |
| ADDITIVES | | method | limit/base | current | history1 | history2 |
| Boron | ppm | ASTM D5185m | | 0 | | |
| Barium | ppm | ASTM D5185m | | 0 | | |
| Molybdenum | ppm | ASTM D5185m | | 0 | | |
| Manganese | ppm | ASTM D5185m | | 0 | | |
| Magnesium | ppm | ASTM D5185m | | 7 | | |
| Calcium | ppm | ASTM D5185m | | 25 | | |
| Phosphorus | ppm | ASTM D5185m | | 352 | | |
| Zinc | ppm | ASTM D5185m | | 191 | | |
| Sulfur | ppm | ASTM D5185m | | 6161 | | |
| CONTAMINANTS | | method | limit/base | current | history1 | history2 |
| Silicon | ppm | ASTM D5185m | >15 | <1 | | |
| Sodium | ppm | ASTM D5185m | | <1 | | |
| Potassium | ppm | ASTM D5185m | >20 | 0 | | |
| Water | % | ASTM D6304 | >0.05 | 0.003 | | |
| ppm Water | ppm | ASTM D6304 | >500 | 32 | | |
| FLUID CLEANLIN | IESS | method | limit/base | current | history1 | history2 |
| Particles >4µm | | ASTM D7647 | | 1030 | | |
| Particles >6µm | | ASTM D7647 | >1300 | 256 | | |
| Particles >14μm | | ASTM D7647 | >160 | 20 | | |
| Particles >21µm | | ASTM D7647 | >40 | 6 | | |
| Particles >38µm | | ASTM D7647 | >10 | 1 | | |
| Particles >71µm | | ASTM D7647 | >3 | 0 | | |
| Oil Cleanliness | | ISO 4406 (c) | >17/14 | 15/11 | | |
| FLUID DEGRADA | TION | method | limit/base | current | history1 | history2 |

Acid Number (AN)

mg KOH/g ASTM D8045

0.36 ---



OIL ANALYSIS REPORT

