

# **OIL ANALYSIS REPORT**

Sample Rating Trend



Machino Id

# KAESER ASD 25T 4101564 (S/N 1006)

Component

Compressor

KAESER SIGMA (OEM) S-460 (--- GAL)

#### DIACNOCIO

#### Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

#### Wear

All component wear rates are normal.

## Contamination

There is a moderate amount of particulates present in the oil.

### **Fluid Condition**

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jul2014 Oct20	116 Oct2017 Jun2018	Nov2019 Nov2020 Oct2021 Nov2	022 Oct202:	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA007529	KCPA003455	KCP47875D
Sample Date		Client Info		16 Oct 2023	12 Jun 2023	18 Nov 2022
Machine Age	hrs	Client Info		51820	50185	47738
Oil Age	hrs	Client Info		0	0	3123
Oil Changed		Client Info		N/A	N/A	Changed
Sample Status				ATTENTION	ABNORMAL	ABNORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	0	2	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	2	1	2
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	0
Barium	ppm	ASTM D5185m	90	0	6	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	90	62	61	74
Calcium	ppm	ASTM D5185m	2	<1	0	<1
Phosphorus	ppm	ASTM D5185m		0	0	3
Zinc	ppm	ASTM D5185m		0	6	3
Sulfur	ppm	ASTM D5185m		21323	18573	20764
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	<1
Sodium	ppm	ASTM D5185m		22	16	14
Potassium	ppm	ASTM D5185m	>20	4	3	8
Water	%	ASTM D6304	>0.05	0.017	0.025	0.027
ppm Water	ppm	ASTM D6304	>500	174	251.8	272.1
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		6351	16228	4152
Particles >6µm		ASTM D7647	>1300	<b>1648</b>	<b>▲</b> 3276	<u></u> 1652
Particles >14µm		ASTM D7647	>80	113	121	<u> </u>
Particles >21µm		ASTM D7647	>20	25	19	<u></u> 55
Particles >38µm		ASTM D7647	>4	0	0	4
Particles >71µm		ASTM D7647		0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	00/18/14	<u>^</u> 21/19/14	▲ 19/18/15
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	0.4	0.37	0.36	0.33



## **OIL ANALYSIS REPORT**

