


OIL ANALYSIS REPORT

KAESER BSV 100 1843470 (S/N 1145)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)





DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil. Moderate concentration of visible dirt/debris present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Oct2020	Mar2023	Sep 2023 Dec 2023	Mar2024	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA013752	KCPA011448	KCPA00076
Sample Date		Client Info		15 Mar 2024	20 Dec 2023	11 Sep 2023
Machine Age	hrs	Client Info		18980	18573	18365
Oil Age	hrs	Client Info		500	0	0
Oil Changed		Client Info		Not Changd	N/A	N/A
Sample Status				ABNORMAL	NORMAL	ATTENTION
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	0	<1
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m	>10	<1	0	0
Lead	ppm	ASTM D5185m	>10	0	0	0
Copper	ppm	ASTM D5185m	>50	0	1	0
Tin	ppm	ASTM D5185m	>10	0	0	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	90	97	101	108
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	0	0
Magnesium	ppm	ASTM D5185m	100	96	93	105
Calcium	ppm	ASTM D5185m	0	2	0	4
Phosphorus	ppm	ASTM D5185m	0	0	0	0
Zinc	ppm	ASTM D5185m	0	0	0	0
Sulfur	ppm	ASTM D5185m	23500	22544	19261	23704
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	3	<1
Sodium	ppm	ASTM D5185m		6	9	7
Potassium	ppm	ASTM D5185m	>20	0	0	0
Water	%	ASTM D6304	>0.05	0.014	0.021	0.015
ppm Water	ppm	ASTM D6304	>500	141	216	150.1
FLUID CLEANLIN	ESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		13593		8899
Particles >6µm		ASTM D7647	>1300	<u>^</u> 3049		2024
Particles >14μm		ASTM D7647	>80	<u> </u>		83
Particles >21μm		ASTM D7647	>20	<u>^</u> 30		17
Particles >38μm		ASTM D7647	>4	0		1
Particles >71µm		ASTM D7647	>3	0		0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>21/19/14</u>		20/18/14
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	ma 1/011/a	ACTM DOOM	1.0	0.20	0.40	0.40

Acid Number (AN)

mg KOH/g ASTM D8045 1.0

0.42

0.39

0.40



OIL ANALYSIS REPORT

