

OIL ANALYSIS REPORT

Sample Rating Trend



KAESER AIRCENTER SM 10 6163615 (S/N 1003)

Compressor

KAESER SIGMA (OEM) M-460 (--- GAL)

DIAGNOSIS

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a high amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Nov2018	Jul2020 Jun2021	Dec2021 Sep2022 Ma	m2023	
SAMPLE INFORM	MATION	method	limit/base	current	history1	history2
Sample Number		Client Info		KCPA013684	KCPA000375	KCP50677
Sample Date		Client Info		01 Mar 2024	17 Mar 2023	20 Dec 2022
Machine Age	hrs	Client Info		29830	28513	27905
Oil Age	hrs	Client Info		1400	0	1300
Oil Changed		Client Info		Not Changd	N/A	Changed
Sample Status				ABNORMAL	ABNORMAL	NORMAL
WEAR METALS		method	limit/base	current	history1	history2
Iron	ppm	ASTM D5185m	>50	0	<1	0
Chromium	ppm	ASTM D5185m	>10	0	0	0
Nickel	ppm	ASTM D5185m	>3	0	0	0
Titanium	ppm	ASTM D5185m	>3	0	0	0
Silver	ppm	ASTM D5185m	>2	0	2	0
Aluminum	ppm	ASTM D5185m		0	1	0
Lead	ppm	ASTM D5185m	>10	0	<1	0
Copper	ppm	ASTM D5185m		18	2	2
Tin	ppm	ASTM D5185m	>10	0	<1	0
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m	0	0	0	0
Barium	ppm	ASTM D5185m	90	0	58	2
Molybdenum	ppm	ASTM D5185m	0	0	0	0
Manganese	ppm	ASTM D5185m		0	<1	0
Magnesium	ppm	ASTM D5185m	100	9	89	65
Calcium	ppm	ASTM D5185m	0	0	3	<1
Phosphorus	ppm	ASTM D5185m	0	0	35	2
Zinc	ppm	ASTM D5185m	0	0	5	13
Sulfur	ppm	ASTM D5185m	23500	21511	21992	21733
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	<1	2	0
Sodium	ppm	ASTM D5185m		3	23	23
Potassium	ppm	ASTM D5185m		0	4	4
Water	%	ASTM D6304		0.006	0.015	0.009
ppm Water	ppm	ASTM D6304	>500	70	151.3	97.6
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4μm		ASTM D7647		9421	10003	924
Particles >6µm		ASTM D7647		<u>^</u> 2110	△ 3136	216
Particles >14μm		ASTM D7647	>80	<u>^</u> 162	<u>192</u>	17
Particles >21μm		ASTM D7647	>20	<u></u> 47	<u>48</u>	3
Particles >38µm		ASTM D7647	>4	1	1	0
Particles >71μm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	<u>20/18/15</u>	<u>^</u> 21/19/15	17/15/11
FLUID DEGRADA	TION	method	limit/base	current	history1	history2
Acid Number (AN)	mg KOH/g	ASTM D8045	1.0	0.34	0.36	0.33



OIL ANALYSIS REPORT

