


OIL ANALYSIS REPORT

Sample Rating Trend



Machine Id KAESER ESD 250 6550978 (S/N 1052)

Compressor

KAESER SIGMA (OEM) FG-460 (--- GAL)

Recommendation

No corrective action is recommended at this time. The filter change at the time of sampling has been noted. Resample at the next service interval to monitor.

Wear

All component wear rates are normal.

Contamination

There is a moderate amount of particulates present in the oil.

Fluid Condition

The AN level is acceptable for this fluid. The condition of the oil is suitable for further service.

		Jun2019	Jun 2020 Jan 202	1 Jui2021 May2022	Dec2023	
SAMPLE INFORM	MATION	method	limit/base		history1	history2
Sample Number		Client Info		KCPA010715	KCP50731	KCP36801
Sample Date		Client Info		27 Dec 2023	31 May 2022	22 Jul 2021
Machine Age	hrs	Client Info		20003	16593	11481
Oil Age	hrs	Client Info		0	5112	2558
Oil Changed	1110	Client Info		N/A	Changed	Changed
Sample Status		Oliciti IIIIO		ATTENTION	NORMAL	NORMAL
WEAR METALS		method	limit/base		history1	history2
Iron	nnm	ASTM D5185m	>50		13	21
Chromium	ppm	ASTM D5185m		8	<1	<1
Nickel	ppm			0	0	
	ppm	ASTM D5185m	>3	0		<1
Titanium	ppm	ASTM D5185m		-	0	<1
Silver	ppm	ASTM D5185m	>2	0	0	0
Aluminum	ppm	ASTM D5185m		3	3	5
Lead	ppm	ASTM D5185m	>10	0	<1	0
Copper	ppm	ASTM D5185m		2	6	11
Tin	ppm	ASTM D5185m	>10	0	0	0
Antimony	ppm	ASTM D5185m				2
Vanadium	ppm	ASTM D5185m		0	0	0
Cadmium	ppm	ASTM D5185m		0	0	0
ADDITIVES		method	limit/base	current	history1	history2
Boron	ppm	ASTM D5185m		0	0	2
Barium	ppm	ASTM D5185m		0	0	0
Molybdenum	ppm	ASTM D5185m		0	0	0
Manganese	ppm	ASTM D5185m		0	0	<1
Magnesium	ppm	ASTM D5185m		0	1	0
Calcium	ppm	ASTM D5185m		0	0	0
Phosphorus	ppm	ASTM D5185m	500	237	178	231
Zinc	ppm	ASTM D5185m		85	81	94
Sulfur	ppm	ASTM D5185m		1295	1113	1321
CONTAMINANTS		method	limit/base	current	history1	history2
Silicon	ppm	ASTM D5185m	>25	0	0	0
Sodium	ppm	ASTM D5185m		<1	0	<1
Potassium	ppm	ASTM D5185m	>20	0	<1	7
Water	%	ASTM D6304	>0.05	0.003	0.007	0.004
ppm Water	ppm	ASTM D6304	>500	31	78.3	46.3
FLUID CLEANLIN	IESS	method	limit/base	current	history1	history2
Particles >4µm		ASTM D7647		4453	1425	2078
Particles >6µm		ASTM D7647	>1300	<u> </u>	319	375
Particles >14μm		ASTM D7647	>80	158	63	27
Particles >21µm		ASTM D7647	>20	55	30	10
Particles >38µm		ASTM D7647	>4	2	2	0
Particles >71μm		ASTM D7647	>3	0	0	0
Oil Cleanliness		ISO 4406 (c)	>/17/13	19/18/14	18/15/13	16/12
FLUID DEGRADA	TION	method	limit/base	current	history1	history2

Acid Number (AN)

mg KOH/g ASTM D8045 1.5

0.80 0.722 Contact/Location: BRIAN MULLIS - DARTHO



OIL ANALYSIS REPORT

